



AMI400



Features

- Fanless system support IBASE MI910E and MB899HF Mini-ITX motherboards
- Available in silver color
- One 2.5" HDD drive bay, PCI slot & 5.25" slim type DVD combo drive (option)
- Fanless operation
- Supports desktop or wall mount mounting

Specifications

System Mainboard	MI910E, MB899HF
Construction	Aluminum & Steel
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	MI910E (audio, 1x LAN, 4x USB, COM, VGA, SPDIF, 1394, KB/MS), MB899HF (audio, 2x LAN, 4x USB, COM, VGA, TV out, SPDIF, 1394, KB/MS)
Storage	1x 2.5" HDD drive bay, optional 1x 5.25" slim type DVD combo
Mounting	Desktop or wall mount
Dimensions	267mm(W) x 109mm(H) x 263.5mm(D)
Power Supply	110W DC to DC converter & 150W adaptor
Expansion Slot	PCI

Environmental/Mechanical

Operating Temperature	0°C ~ 45°C
Storage Temperature	-20° ~ 80°C
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 0.25 grms/5~500Hz random operation
RoHS Compliance	Available

Ordering Information

AMI400-8	Fanless system for MB899HF Mini-ITX motherboard, w/ Intel® Celeron® M 440, 1.83GHz, 1GB RAM, 80GB HDD, 110W DC-DC converter, 150W power adaptor, 2.5" HDD holder
AMI400-9	Fanless system for MI910E Mini-ITX motherboard, w/ Intel® Core™2 Duo T7500, 2.2GHz, 2GB RAM, 80GB HDD, ID392 DVI, 110W DC-DC converter, 150W power adaptor, 2.5" HDD holder



Remarks: 1. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.
2. ODM/OEM is available.
3. Specifications are subject to change without prior notice.