

# Industrial Motherboard


## Full Size ATX motherboard P4BWA

Support Intel Core 2 Quad with DDRII

Onboard VGA, 2 x Gigabit LAN

10 x USB2.0, Realtek ALC888 HD Audio

6 x COM Ports, GPIO, SATA, ISA Slots



<b>Form Factor</b>	Full size ATX motherboard
<b>CPU</b>	Support Intel® Core™ 2 Quad / Core™ 2 Duo / Pentium® D / Pentium® 4 processor Package type: PLGA 775 Front side bus: 533/800/1066MHz Dual core, EM64T supported
<b>Memory</b>	4 x DDRII 533/667/800MHz SDRAM up to 8GB
<b>Chipset</b>	Intel Q965 & ICH8DO
<b>Real Time Clock</b>	Chipset integrated RTC with onboard lithium battery
<b>Watchdog Timer</b>	Generates a system reset with internal timer for 1min/s ~ 255min/s
<b>Power Management</b>	ACPI 1.0 compliant, supports power saving mode with ATX PSU
<b>VGA Interface</b>	Intel integrated extreme GMA3000 (Graphic Media Accelerator) Technology
<b>Video Memory</b>	Up to 256MB shared with system memory
<b>Serial ATA Interface</b>	6 x serial ATAII interface with 300MB/s transfer rate Support RAID 0, 1, 5, 10 and Intel Matrix Storage Technology
<b>Audio Interface</b>	Intel integrated with Realtek ALC888 HD Audio
<b>LAN Interface</b>	2 x Intel 82573L Gigabit LAN
<b>GPIO interface</b>	Onboard programmable 8-bit Digital I/O interface
<b>Extended Interface</b>	Onboard one x16 PCI-Express, one x4 PCI-Express One Mini-PCI, four PCI slots and two ISA slots.
<b>Internal I/O Port</b>	4 x RS232 ports, 1 x RS232/422/485, 1 x Parallel port, 1 x FDD port, 1 x GPIO port, 1 x IrDA, 4 x USB ports, 1 x Front Audio connector, 1 x CDIN connector,
<b>External I/O Port</b>	1 x PS/2 Keyboard/Mouse Port, 2 x RJ45 LAN ports, 6 x USB2.0 ports 1 x DB15 VGA port, 1 x Serial Port, 1 x SPDIF, 1 x Audio.
<b>Power Requirement</b>	Standard 24-pin ATX power supply (20-pin is compatible) Standard 8-pin 12V power Input connector (4-pin is compatible)
<b>Dimension</b>	307mm x 244mm (L x W)
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20~85 centigrade

### Ordering Code

<b>P4BWA</b>	Support Intel Core 2 Quad LGA775 with DDRII, Onboard VGA, Dual Intel Gigabit LAN 10 x USB2.0, Realtek ALC888 HD Audio, 6 x COM Ports, GPIO, SATA and 2 x ISA slots.
--------------	--

### Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Xintai 5th Rd., Xizhi Dist, New Taipei City 22102, Taiwan.

TEL: +886-2-26963909

Website: [www.comnell.com.tw](http://www.comnell.com.tw)

FAX: +886-2-26963911

E-mail: [info@connell.com.tw](mailto:info@connell.com.tw)