



testo 317-3

## CO Monitor

Carbon monoxide warning in the surrounding area

NEW!

CO



## Application, details and accessories for testo 317-3



Technical data	
Measurement range	0 to +1999 ppm CO
Resolution	1 ppm
Accuracy	±10 ppm (0 to +99 ppm) ±10 % (+100 to +499 ppm) ±20 % (>500 ppm)
Response time (t <sub>90</sub> )	40 s
Supply voltage	2 batteries Type AAA
Battery life	150 h (with beeper switched off)
Ambient temperature	-5 to +45 °C
Warranty	2 years on the instrument 3 years on the CO sensor

The testo 317-3 CO monitor detects the presence of carbon monoxide in the surrounding area and warns the user both visually and audibly about the dangerous gas concentrations e.g. when installing and servicing gas heaters.

### Special features:

- 3 year warranty on CO cell
- Visual and audible alarm
- No zero phase, instrument can be used immediately
- Adjustable alarm threshold
- CO zeroing at site

### Ordering data for testo 317-3



### Quick Fax Order

Qty.	Item	Part no.	
	CO Monitor testo 317-3 incl. leather bag, headphones, hand strap, self-test function, scanner	0632.3173	

To:

Sender

\_\_\_\_\_  
Name

\_\_\_\_\_  
Company

\_\_\_\_\_  
Department

\_\_\_\_\_  
Address

\_\_\_\_\_  
Date, Signature