

## Versatile thermometer for industry

Affordable and robust.

The versatile testo 925 thermometer is the ideal partner for tough applications when taking daily temperature measurements in industry. The indestructible TopSafe case protects the instrument from dirt, water and impact.



Surface temperature in moulding tools

Probes  
HOLD  
-50 to +1000°C



- Easy to read thanks to large display
- Hold key to suspend the reading
- More than 25 robust probes for every application
- TopSafe, protection case, for tough applications

### testo 925

testo 925, thermometer, incl. battery and calibration protocol

Part no. 0560 9255

### Technical data

#### Special technical data for testo 925 only:

Probe type	Type K (NiCr-Ni)
Meas. range	-50... +1000 °C
Accuracy ± 1 digit	±(0.7 °C ±0.5% of mv) (-40... +900 °C) ±(1 °C ±1% of mv) (-50... -40.1 °C) ±(1 °C ±1% of mv) (+900.1... +1000 °C)
Resolution	0.1 °C (-50... +199.9 °C) 1 °C (+200... +1000 °C)
Display	LCD, 1 line

See next two pages for more data.

## Differential thermometer for the trades

testo 922 can measure the temperatures of two probes simultaneously and display the differential temperature.

The affordable differential thermometer is ideal for use by heating and air conditioning technicians and fitters. TopSafe, the indestructible case protects the instrument from dirt and impact.



Checks flow/return in heating systems

2 probe sockets  
Probes  
HOLD  
-50 to +1000°C



- 2 probes can be connected (Type K)
- Display for T1, T2 and differential temperature
- HOLD button to suspend reading
- TopSafe, protects instrument from dirt and impact

### testo 922

testo 922, thermometer, incl. battery and calibration protocol

Part no. 0560 9224

### Technical data

#### Special technical data for testo 922 only:

Probe type	Type K (NiCr-Ni)
Meas. range	-50... +1000 °C
Accuracy ± 1 digit	±(0.7 °C ±0.5% of mv) (-40... +900 °C) ±(1 °C ±1% of mv) (-50... -40.1 °C) ±(1 °C ±1% of mv) (+900.1... +1000 °C)
Resolution	0.1 °C (-50... +199.9 °C) 1 °C (+200... +1000 °C)
Display	LCD, 1 line
Chann. external	2 (var.)

See next two pages for more data.