

HMP155 Humidity and Temperature Probe

with resistive 4-wire output for temperature

| | | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | |
|---|--|-------------|---|---|--------|---|---|--------|---|---|------------------|----|----|----|-------------|------------------|-------|
| Vaisala HUMICAP® Humidity and Temperature Probe | | HMP155 | | | | | | | | | | | | | | | |
| 1. Probe type | Voltage output for RH (RS485 for service use), 4-wire Pt100 output for Temperature | D | | | | | | | | | | | | | | | Price |
| 2. Signal output selection | 0...1 V output 0...5 V output 0...10 V output | 2 3 4 | | | | | | | | | | | | | | | |
| 3. Analog output signal for CH1 | None (4-wire PT100 output used) | | A | | | | | | | | | | | | | | |
| 4. Analog output signal for CH2 | RH (0... 100%RH) | | | B | | | | | | | | | | | | | |
| 5. Units (RS485 in service use) | Metric Non-metric | | | | 1 2 | | | | | | | | | | | | |
| 6. Humidity sensor type | General purpose General purpose | | | | | | | 1 3 | | | | | | | | | |
| 7. Heating options | None | | | | | | | | A | | | | | | | | |
| 8. Chemical purge | None | | | | | | | | | 0 | | | | | | | |
| 9. Sensor protection | Sintered Teflon filter | | | | | | | | | | A | | | | | | |
| 10. Probe cable length | No cable (no counter connector) 3.5 m (with 8 pin M12 female connector) 10 m (with 8 pin M12 female connector) 30 m (with 8 pin M12 female connector) | | | | | | | | | | 0 1 2 3 | | | | | | |
| 11. Additional Temperature probe | None | | | | | | | | | | | A | | | | | |
| 12. Calibration | At room temperature | | | | | | | | | | | | 1 | | | | |
| 13. PC-Accessories | None PC connection cable (USB) MI70 connection cable PC connection cable (USB) & MI70 connection cable | | | | | | | | | | | | | | | A B C D | |
| 14. Installation accessories | None Installation kit to Stevenson screen | | | | | | | | | | | | | | | 0 1 | |
| 15. (For production use only) | | | | | | | | | | | | | | | | A | |
| | | | | | | | | | | | | | | | Total | | |
| | | | | | | | | | | | | | | | QTY | | |
| | | | | | | | | | | | | | | | Total value | | |

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings:

| | | | | | | | | | | | | | | | |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| HMP155 | D | 2 | A | B | 1 | 1 | A | 0 | A | 1 | A | 1 | A | 0 | A |
|--------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|

End customer: _____

ESIS Pty Ltd
 Ph 02 9481 7420 www.esis.com.au
 Fax 02 9481 7267
 PO Box 450, Pennant Hills NSW 2120