

TKG-086-MB-IP68-BACKL

	Esis Pty Ltd
	Ph 02 9481 7420
	Fax 02 9481 7267
	www.esis.com.au



Features and benefits:

- LED powered backlight function
- Long LED lifetime and low power consumption
- 8-level dimmer controlled by arrow keys
- Gold on gold domes
- Extreme temperature range of -40°C to +90°C
- Positive tactile feedback
- Integrated mouse button
- PS/2 and USB compatible
- 19 inch 1U drawer compatible units
- Rugged construction for reliable functionality
- Special Dura-coating for excellent mechanical and chemical resistance

Specification Keyboard

Number of Keys: 86
 Keyswitch Technology: Gold opn gold domes
 Activation Force/ -Travel: 3,0 N / 0,35 mm
 Keyswitch Lifetime: 2 mil. Operations
 Protection Level: IP68, NEMA 6P
 Mounting Type: desktop
 Dimensions: 320 x 147 x 20 mm
 12,6" x 5,79" x 0,79"
 Weight: 950 g
 Operating Temperature: -40 °C to 90 °C;
 -40 °F to +194 °F

Specification Mousebutton

Number of keys: 2
 Motion detection method: hall sensor
 Resolution: 800 dpi
 Protection Level: IP68, NEMA 6P
 Enclosure Colour: similar RAL9017

Cat.-No.	Product Name	
KG13009	TKG-086-MB-IP68-BACKL-PS/2-US	PS/2; US-Layout
KG13011	TKG-086-MB-IP68-BACKL-USB-US	USB; US-Layout
Other language versions/interfaces/configuration available on request		