

DATA LOGGERS

Simple Logger® II TRMS Clamp-On Current

Model CL601

Designed for plant and field service applications and for use in harsh environments

► SPECIFICATIONS

MODEL	CL601
ELECTRICAL	
Channels	One
Input	Split CT – AC Current
Measurement Range	0 to 600Aac
Resolution	0.1A
Accuracy (50/60Hz)	0 to 5A: unspecified 5 to 50A: ±(1% of Reading + 1A) 50 to 400A: ±(1% of Reading + 0.5A) 400 to 600A: ±(3% of Reading + 1A)
Sample Rate	64 samples/cycle
Storage Rate	Programmable from 8 every second to 1 every day
Storage Modes	Start/Stop, FIFO, Extended Recording Mode (XRM™)* and Alarm
Recording Length	15 minutes to 8 weeks, programmable using DataView®
Memory	240,000 measurements (512KB) - The recorded data is stored in non-volatile memory and will be retained even if the battery is low or removed.
Communication	USB 2.0 optically isolated
Power Source	2 x 1.5V AA-cell Alkaline batteries (included)
Battery Life	100 hours to >45 days (dependent on sample rate and recording length)
MECHANICAL	
Dimensions	9.25 x 4.0 x 1.63" (235 x 102 x 41mm)
Max Conductor Size	1 conductor - Ø 1.42" (36mm) 2 conductor - Ø 1.00" (25mm) ea
Weight (with battery)	17.1 oz (485g)
Case	UL94-V0
Vibration	IEC 68-2-6 (1.5mm, 10 to 55Hz)
Shock	IEC 68-2-27 (30G)
Drop	IEC 68-2-32 (1m)

***Extended Recording Mode (XRM™)**

This unique recording mode provides the opportunity to continuously record over long periods of time by reducing the stored samples of the oldest data and maintaining matching resolution for the newest data. Each time the memory fills up using XRM™ every other of the oldest stored samples is discarded making room for newer samples. This process continues until the recording is manually stopped.



www.esis.com.au
Ph 02 9481 7420
Fax 02 9481 7267
esis.enq@esis.com.au

ESIS
Industrial Electronics



► FEATURES

- 0 to 600Arms
- True RMS measurements
- Self contained, no exposed connections
- Overload indication
- Isolated USB 2.0 communication cable included
- One button operation
- Alarm function
- 5 LED indicators quickly and clearly display logger status
- Powered by standard Alkaline batteries
- Includes FREE DataView® software for data storage, real-time display, analysis and report generation
- EN 61010-1; 300V CAT IV, 600V CAT III

► APPLICATIONS

- Machine load monitoring
- HVAC troubleshooting
- Load profiling
- Electrical troubleshooting
- Start-Stop time stamping

CATALOG NO.	DESCRIPTION
-------------	-------------

2126.01	Simple Logger® II Model CL601 (1-Channel, TRMS Clamp-On, 600Aac, DataView® software)
---------	--