Panasonic recommends Windows 8 Pro



TOUGHBOOK CF-C2MK2

SEMI-RUGGED CONVERTIBLE TABLET PC WITH DIGITISER AND MULTI-TOUCH DISPLAY

One of the most durable and flexible business convertible PCs in the market, the Windows 8-equipped Toughbook CF-C2 combines desktop performance, world-class connectivity and advanced mobility features to provide the ideal tool for mobile workers. A unique triple hinge design enhances ruggedness and smoothness when the screen is rotated, and an ergonomic handstrap helps prevent accidental drops. Multiple expansion options and ports, coupled with an outdoor IPS display with a capacitive touchscreen make the CF-C2 a device that's ready to perform both out in the field or in the office.



DUGHPAI

- Intel[®] Core[™] i5-4300U vPro[™] Processor
- Windows 8.1 Pro 64-bit
- * 12.5-inch HD (1366x768) 500cd/m² high brightness IPS Display
- 10-finger capacitive multi touch screen with digitiser
- Withstands drops from a height of 76cm*
- Spill resistant keyboard, and touchpad**
- Robust magnesium alloy casing
- Shock-protected HDD
- Ergonomic handstrap
- Battery life up to 14 hours (mobile mark 2007)
- Hot swappable battery function for continuous use
- LAN, SDXC card slot, USB 3.0 x2, USB 2.0 x2, HDMI
- Optional integrated 4G/LTE
- Optional serial port or VGA, express card, smartcard reader, and NFC
- Built-in security chip (TPM v1.2) for data protection
- * Carried out in Panasonic technical research lab. Test conducted in non-operating condition.
- ** Spill resistance applies to all of the keyboard. It does not apply to the side panel, battery section, speakers, and DVD drive when it is open. The spill-resistant performance of the product does not guarantee that it will be free from damage or malfunction. If water is spilled onto it, be sure to have it repaired.





Panasonic recommends Windows 8 Pro

TOUGHPAD CF-C2MK2

SEMI-RUGGED MOBILE CONVERTIBLE TABLET PC WITH DIGITISER AND MULTI-TOUCH DISPLAY



The Toughbook CF-C2 is a specialist business tool, thanks to a range of business expansion and configuration options. With express card, smart card, VGA and modem ports, and an optional serial port for diagnostic and measurement work on legacy devices, the CF-C2 is capable of meeting the needs of almost every organisation.









*Windows 7 Drivers available **Option combinations are varied. Please consult with your local rep for further info. ***Carried out in Panasonic technical research lab. Test conducted in non-operating condition. Intel, the Intel logo, Intel Core, Intel vPro, Core Inside and vPro Inside are trademarks of Intel Corporation in the U.S. and other countries. Microsoft® and Windows® are registered trademarks of Microsoft® Corporation of the United States and/or other countries. All other brand names shown are the registered trademarks of the relevant companies. All rights reserved. All working conditions, times and figures quoted are optimum or ideal levels and may differ as a result of individual and local circumstances. Specifications are subject to change without notice. Publication date: July 2014.

| Mobile Computing Platform | Intel® Core™ i5-4300U vPro™ Processor 1.9GHz with Intel® Turbo Boost up to 2.9GHz, 3MB Cache | |
|---|---|---------------------------------------|
| Operating System | Windows 8.1 Pro 64-bit* | |
| RAM | 4GB DDR3L SDRAM (max 8GB not user upgradable) | |
| Graphics Chip | Intel® HD Graphics 4400 (built-in chipset) | |
| web Camera | HD 1280 x 720, 30 fps | |
| Storage | 500 GB SATA HDD, 5400rpm | |
| Display | 12.5" WXGA 1366 x 768 IPS Display | |
| Display | Up to 500cd/m ² brightness | |
| | 10 finger multi touchscreen with digitiser | |
| | Version 4.0 + EDR Class 1 | |
| WLAN | IEEE WiFi 802.11 a/b/g/n (Intel Dual Band Wireless N 7260) | |
| 4G/LTE Mobile Broadband (optional)** | Optional Sierra Wireless MC7305 | |
| Sound | Built-in Mono Speaker | |
| Interface Standard | LAN (RJ45 1000M/100M/10Mbps) | Headphone Output |
| | SDXC Memory Card Slot | Microphone Input |
| | USB 3.0: x2, USB 2.0 x1 | Docking Connector (dedicated 100-pin) |
| | HDMI | |
| Interface Options* | Rear Option: VGA or Serial or Modem | |
| | Bottom Option: Rear Camera (HD 1280 x 720, 30 fps) or Half Size Smart Card or NFC | |
| | Left Option: Express Card Slot or Full Size Smart Card | |
| Power | Standard Battery: Li-Ion 6 cell 10.8V, 6400mAh (typical) - CF-VZSU80U | |
| | Optional Large Battery: Li-Ion 9 cell 10.8V, 8700mAh (typical) - CF-VZSU83U | |
| | Hot Swappable Battery function | |
| | Operating Time: Up to 14 hours (standard battery), 19 hours (large battery) | |
| | Charging Time: 2.5 hours | |
| Security Features | TPM (Trusted Platform Module, TCG V1.2 compliant), Integrated Kensington cable security lock slot, Optional SmartCard reader | |
| Physical Dimensions | 299mm (W) x 217mm (H) x 25-42mm (D) | |
| Veight | Approx 1.81kg | |
| Dperating Temperature | 0° - 50° C | |
| Accessories | AC Adapter: CF-AA6413AM | |
| | Standard 6 cell Battery: CF-VZSU80U | |
| | Large 9 cell Battery: CF-VZSU83U | |
| | Port Replicator: CF-VEBC21U - USB 3.0 x4, LAN, VGA, HDMI x2, Optical Drive, Kensington Lock | |
| | Battery Charger: CF-VCBTB3W | |
| | 12.5" Screen Protective Film: CF-VPF25U Capacitive Stylus: CF-VNP020AU | |
| | Digitiser Stylus: CF-VNP016AU | Tether: CF-VNT004U |
| Ruggedness | Gravity drop resistance test: 76cm*** | |
| | 100kgf Pressure*** | |
| | Spill Resistant Keyboard | |
| | Shock mounted HDD with floating connectors | |
| | Magnesuim Alloy Chassis | |
| | | |

Dealer Details:



www.esis.com.au

Ph 02 9481 7420 Fax 02 9481 7267 esis.enq@esis.com.au



TOUGHPAD