

Getac

Rugged Mobile Computing Solutions

X500

Fully Rugged Notebook



- Intel® Core™ i7-4600M vPro™ Processor
- 15.6" TFT LCD FHD with Getac QuadraClear® Sunlight Readable Display
- Optional NVIDIA® GeForce® 745M 2GB Discrete Graphic Controller
- Multimedia Bay & PCI/PCIe Expansion Unit



PCI/PCI-Express
Expansion Unit



Multimedia Bay
2nd HDD



Rugged Mobile Computing Solutions

X500 Fully Rugged Notebook

Getac recommends Windows.



Specifications

Operating System	Windows® 7 Professional Windows® 8 Professional	Docking connector (80-pin) x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN
Mobile Computing Platform	Intel® Core™ i7 vPro™ Technology - Intel® Core™ i7-4600M vPro™ Processor 2.9GHz, Max 3.6GHz, with Intel® Turbo Boost Technology - 4MB L3 Intel® Smart Cache - Mobile Intel® QM87 Express chipset Intel® Core™ i5 vPro™ Technology - Intel® Core™ i5-4300M vPro™ Processor 2.6GHz, Max. 3.3GHz with Intel® Turbo Boost Technology - 3MB L3 Intel® Smart Cache - Mobile Intel® QM87 Express chipset	Communication Interface 10/100/1000 base-T Ethernet Intel® Dual Band Wireless-AC 7260, 802.11ac Bluetooth® (v4.0 class 1) ⁱⁱ Optional SiRFstarIV™ GPS Optional Gobi™ mobile broadband
VGA Controller	Intel® HD Graphics 4600 ⁱ Optional NVIDIA® GeForce® 745M 2GB discrete graphic controller	Software Getac Utility Adobe® Reader®
Display	15.6" TFT LCD FHD (1920 x 1080) Optional 800 nits QuadraClear® sunlight readable display with touchscreen	Security Feature Intel® vPro™ Technology TPM 1.2 Fingerprint scanner Smart card reader Kensington lock
Storage & Memory	8GB DDR3 expandable to 16GB SATA HDD 500GB Optional SATA SSD 128GB / 256GB	Power AC adapter (90W, 100-240VAC, 50 / 60Hz) Li-Ion smart battery (10.8V, 8700mAh) ⁱⁱⁱ Optional Multimedia Bay 2nd Li-Ion smart battery (10.8V, 8700mAh)
Keyboard	LED backlit membrane keyboard with integrated numeric keypad Optional LED backlit rubber keyboard	Dimension (W x D x H) & Weight 410 x 290 x 65mm (16.1" x 11.4" x 2.5") 5.2 kg (11.4 lbs) ^{iv}
Pointing Device	Touchscreen - Optional pressure sensitive touchscreen Touchpad - Glide touchpad with scroll bar	Rugged Feature MIL-STD-810G certified and IP65 certified MIL-STD-461F certified ^v Optional ANSI/ISA 12.12.01 ^{vi} Full magnesium alloy case Shock-protected removable HDD Vibration & drop resistant
Expansion Slot	PCMCIA Type II x 1 ExpressCard/54 x 1 Smart card reader x 1 SD Card Reader x 1	Environmental Specification Temperature ^{vii} : - Operating: -20°C to 55°C / -4°F to 131°F - Storage: -40°C to 71°C / -40°F to 160°F Humidity: - 95% RH, non-condensing
Multimedia Bay	DVD super multi drive Optional 2nd battery Optional 2nd storage: HDD 500GB ; SSD 128 GB / 256 GB	Accessories Backpack Battery Charger Vehicle Adapter (90W, 11-16VDC and 22-32VDC) MIL-STD-461F certified AC adapter (90W, 100-240VAC) Stylus and tether Protection film PCI or PCI-Express Expansion Unit (x 2 slots) Main battery (10.8V, 8700mAh) AC adapter (90W, 100-240VAC) Multimedia bay 2nd battery (10.8V, 8700mAh) Multimedia Bay 2nd HDD Vehicle dock Office dock
I/O Interface	Serial port (9-pin; D-sub) x 2 External VGA (15-pin; D-sub) x 1 Microphone (Mini-jack) x 1 Audio output (Mini-jack) x 1 DC in Jack x 1 USB 3.0 (9-pin) x 2 USB 2.0 (4-pin) x 1 USB 2.0 / eSATA Combo x 1 LAN (RJ45) x 2 IEEE 1394a x 1 HDMI x 1	

Docking Solutions

	Dimension W x D x H	Serial Port	External VGA	Microphone	Audio Output	DC in Jack	USB	LAN	Video Capture	DVI	RF antenna connector
Vehicle Dock	410 x 332 x 125 mm (16.4" x 13.1" x 4.9")	2	1	1	1	1	4	1	1	--	3 (optional)
Office Dock	438.4 x 154 x 62 mm (17.2" x 6.1" x 2.4")	1	1	1	1	1	4	1	--	1	--

ⁱ Share memory size may vary by different operating system and RAM size.

ⁱⁱ Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.

ⁱⁱⁱ Battery life testing conducted under BatteryMark 4.0.1. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions.

^{iv} The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

^v Weight varies from configurations and optional accessories.

^{vi} MIL-STD-461F 90W AC adapter sold separately.

^{vii} PCI expansion unit or PCI-E option is not available with ANSI / ISA 12.12.01 configurations.

^{viii} Tested by a national independent third party test lab following MIL-STD-810G.

Getac



Getac Technology Corporation

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist.,
Taipei City, 11568, Taiwan, R.O.C.

Tel: +886 2 2785 7888

globalmarketing@getac.com

www.getac.com

Copyright © 2014 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
All specifications are subject to change without notice. V06M12Y14WW



Industrial Electronics

www.esis.com.au

Ph 02 9481 7420

Fax 02 9481 7267

esis.enq@esis.com.au