



Order form  
Orderer

Valid from September 2007  
Order no.

## DM70 Hand-held Dewpoint Meter

Vaisala DRYCAP® Hand-held Dewpoint Meter		DM70							1	PRICE
Indicator type	no indicator* rechargeable with Euro AC-adaptor rechargeable with UK AC-adaptor rechargeable with US AC-adaptor rechargeable with AUS AC-adaptor alkaline batteries only	A B C D E K								
Indicator accessories	<b>no indicator accessories</b> <i>MI70LINK software with RS232 cable</i> <i>analog output-signal cable</i> <i>MI70Link with RS232 and analog output signal cables</i> <i>MI70LINK software with USB cable</i>	0 1 2 3 5								
Probe type	<b>DMP74A -40...+60°C Td</b> <b>DMP74B -60...+20°C Td</b> <b>DMP74C -50...+20°C Td</b> <i>(for SF6 gas)</i>	A B C								
Probe accessories	<b>no accessories</b> <i>sampling cell DSC74</i> <i>portable sampling system with case (DSS70A)</i> <i>sampling cell DMT242SC</i> <i>sampling cell DMT242SC2 with Swagelok connectors</i> <i>two-pressure sampling cell DSC74B</i> <i>two-pressure sampling cell with coil DSC74C</i>	0 1 2 3 4 5 6								
Connection cable to a transmitter	<b>no connection cable</b> <i>connection cable to DMT242 transmitter</i> <i>connection cable to DMP248 transmitter</i> <i>connection cable to DMT142 transmitter</i> <i>connection cable to DMT340 series transmitter</i> <i>connection cables to DMT340 &amp; DMP248 &amp; DMT242 &amp; DMT142</i>	A B C D E M								
Carrying case	<b>no carrying case**</b> <i>carrying case MI70CASE (Black ABS), for one probe</i> <i>carrying case MI70CASE2 (Aluminium), for two probes</i>	0 1 2								
User's guide	<b>None</b> <b>English</b> <b>German</b> <b>French</b> <b>Japanese</b> <b>Chinese</b>	A B C D J L								
Special features	<b>Standard</b>								1	
									TOTAL	
									QTY	
									TOTAL VALUE	

\* select item A, if only probe is ordered

\*\* select item 0, if portable sampling system is selected

**Selections in bold are included in the prices of the basic versions.**

*Selections in italic are available at an extra price.*

Example of order code with typical settings:

**DM70 B 1 B 1 A 0 B 1**

End customer: \_\_\_\_\_

Extra option : 10m extension cable for probe (213107SP)

**ESIS Pty Ltd**

Ph 02 9481 7420 www.esis.com.au

Fax 02 9481 7267

PO Box 450, Pennant Hills NSW 2120