

DMT132 Dewpoint Transmitter

Vaisala HUMICAP® Dewpoint Transmitter		DMT132		A	A					PRICE
Parameter and scaling 4...20 mA	Dewpoint, scaling -20...+40 °C (-4...104 °F) Dewpoint, free scaling °C Define scale: _____ Dewpoint, free scaling °F Define scale: _____ Tdf atm free scaling °C Define scale: _____ Tdf atm free scaling °F Define scale: _____	A X W Y Z								
Pressure setting for optimized accuracy and Tdf atm calculation	1 bar (abs) 3 bar 5 bar 7 bar special (max 20 bar abs) Define value: _____	1 2 3 4 X								
Settings	Standard			A						
Sensor Protection	Standard tube filter			A						
Cable	no cable <i>0.3 m (1.0 ft) shielded output cable M8, threaded connector</i> <i>3 m (9.8 ft) shielded output cable M8, threaded connector</i> <i>5 m (16.4 ft) shielded output cable M8, threaded connector</i> <i>10 m (32.8 ft) shielded output cable M8, threaded connector</i>	0 1 2 3 4								
Limit LED (Port II)	no LED indication <i>LED with dewpoint setpoint +10 °C (+50 °F)</i> <i>LED with special Td setpoint</i> Define value: _____ °C			A B C						
Installation accessories	no accessories <i>NPT1/2" adapter</i> <i>Basic sampling cell DMT242SC</i> <i>Sampling cell with swagelok 1/4" male connectors DMT242SC2</i> <i>Sampling cell with quick connector and leak screw DSC74</i> <i>Two-pressure sampling cell DSC74B</i> <i>Two-pressure sampling cell with coil DSC74C</i> <i>Duct installation flange DM240FA</i>	0 1 2 3 4 5 6 7								
User's guide language	No user's guide Multilingual guide			A M						
Special features	None								0	
TOTAL										
QTY										
TOTAL VALUE										

*Tdf atm is the dewpoint value calculated back to atmospheric pressure
Below 0 °C the transmitter outputs frostpoint

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

DMT132 A 4 A A 2 A 0 M 0

End customer: _____

Accessories:

226476	Loop-powered display 4...20 mA, Nokeval 301
230602	Tube filter
230914	Special cover set for HMK15 (fits DMT132 and HMP110)
210662SP	NPT Adapter
219690	USB Service cable
219980	Connection cable to DM70/HM70
230388	LED plug
218773	ISO" 1/2 plug
222507	NPT1/2" plug
221525SP	Sealing ring set (3 pcs U-seal)
HUMICAP180R	Humicap180R spare sensor

	www.esis.com.au
	Ph 02 9481 7420 Fax 02 9481 7267 esis.enq@esis.com.au
Industrial Electronics	