Order form Orderer Valid from January 2011 Order no.

## **DMT152 Dewpoint Transmitter**

	Vaisala DRYCAP® Dewpo	int Transmitter			DMT1		Ť			T	Ť		Ť	13	<del></del>	PRICE
1	Mechanical connection	ISO G1/2" thread			Divil	A	+	-	+	+	+	$\vdash$	+	+	_	FRICE
	Mechanical connection	NPT 1/2" thread				В										
		UNF 3/4"-16 thread				C										
_		UNF 5/8"-18 thread				D	.									
2	Measurement parameters	Td/f, ppm					1									
		Td/f, ppm and ppmw for S	F6 gas				2									
3	Analog output Ch1 & Ch2	05 V					В									
	+ RS-485 as standard	010 V					С									
		420 mA					D									
		020 mA					Е									
4	Analog output parameter	Td/f	-80+20 ℃	-112+68 °F				В								
	or function	Td/f	-1000 ℃	-148+ 32 °F				С								
	for Ch1	ppm	0100 ppm					D								
		ppm	0500 ppm					Е								
		Td/f , free scale	Define:	Low	High			х								
		ppm, free scale	Define:	Low	High			Υ								
		ppmw for SF6, free scale		Low	High			F								
		Alarm level on/off output		Parameter	Level			1								
		Frozen output indication of		raiaillelei	Level	_		2								
_	A	Td/f		440 .00 %				_	.							
J	Analog output parameter		-80+20 ℃	-112+68 °F					3							
	or function	Td/f	-1000 ℃	-148+ 32 °F					3							
	for Ch2	ppm	0100 ppm						)							
		ppm	0500 ppm						<b>≣</b>							
		Td/f , free scale	Define:	Low	High				(							
		ppm, free scale	Define:	Low	High				1							
		ppmw for SF6, free scale	Define:	Low	High			ı	=							
		Alarm level on/off output	Define:	Parameter	Level				1							
		Frozen output indication of	on/off*					:	2							
		LED indication on frozen	output**					;	3							
6	Output units	Metric units (Celsius)	•						_ 1							
	·	Non-metric units (Fahrenh	neit)						2							
7	Pressure setting for	None - no ppm output	· ' <b>,</b>							۰ ا						
	ppm calculation	Ambient 1 bara / 14,76 psi	а							1						
	FF 040	Special (max 50 bar abs)		re·	bar					Х						
0	Caraca Destantian	· · · · · · · · · · · · · · · · · · ·														
8	Sensor Protection	Stainless steel mesh filter								-	A					
9	Cable for analog outputs	None									0					
	and power supply	2 m (6.6 ft) cable with snap									1					
	(Port I)	3 m (9.8 ft) shielded cable v									3					
		10 m (32.8 ft) shielded cable									5	1 1		1 1		
	0.11 / 00::	3 m (9.8 ft) cable, M8 thread	ded connector,	90°angle, Ch1 si	gnal + Ch2 LE	υ light					6	1 _			ļ	
10	Cable for RS485 line	None										0				
	and power supply	2 m (6.6 ft) cable with snap-										1				
	(Port II)	3 m (9.8 ft) shielded cable v										3				
		10 m (32.8 ft) shielded cable	e with threaded	connector								5				
11	Installation accessories	None											ו		Ţ	
	ONLY for ISO1/2" thread	Sampling cell DMT242SC										L	)	1 1		
		Sampling cell with swagelok	k 1/4" male con	nectors DMT242S	C2							Ε	<b></b>	1 1		
		Sampling cell with quick cor										F	=			
		Two-pressure sampling cell											3	1 1		
		Two-pressure sampling cell		oil DSC74C									1			
		NW40 flange	Contains of	200. 10									,	1		
	Special features	None											⊔ <sub>A</sub>		ŀ	
12	Package	Standard cardboard												ן גַּ נ		
12	FACKAGE													1 2		
12 13	. acitago	Diantia anno												_		
13	•	Plastic case														
13	User's guide	Plastic case  None  Multilingual quick guide													A X	

 $<sup>^{\</sup>star}$  Indicates by analog signal when measurement is not active (typically sensor purge)

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

| DMT152 | A | 1 | D | B | 2 | 1 | 0 | A | 1 | 0 | 0 | A | 1 | X |

End customer:

accessories

219980 Connection cable for MI70 indicator 219690 USB serial interface cable 221524SP Sealing ring set ISO (copper, 3 pcs) 221563SP Sealing ring set UNF (copper, 3 pcs) 220957SP Stainless steel mesh filter 18 µm 225220SP NW40 Ffange



www.esis.com.au Ph 02 9481 7420 Fax 02 9481 7267

Total value

esis.enq@esis.com.au

<sup>\*\*</sup> For LED indication, choose LED cable in option 9