Order form Orderer Valid from February 2009 Order no.

DMT242 Dewpoint Transmitter

Vaisala DRYCAP® Dewpo	oint Transmitter DM	Г242						PRICE
Dewpoint range	-80+20 ℃ Td, DRYCAP [®] 180M	Α		П			П	
for analog output	-60+60 ℃ Td, DRYCAP [®] 180M	В						
	Free scaling Td, DRYCAP®180M	Х						
	Define Td scale:(℃)							
	-50+50 °C Td, DRYCAP®180S (for refrigerator dryers)	S						
	Free scaling Td °C, DRYCAP®180S (for refrigerator dryers	;) Y						
	Define Td scale:(°C)	•						
Analog Output Cable	No cable - connector only		1					
	2m (6.6 ft) Connection cable with connector		2					
	10 m (33 ft) Connection cable with connector		3					
Pressure setting	1 bar abs			Α				
for optimized	3 bar abs			В				
accuracy	5 bar abs			С				
	7 bar abs			D				
	special (max 20 bar abs) Define value: bar abs			X				
Sensor protection	Stainless steel sintered filter (37 um)				1			
	Stainless steel filter for vacuum				2			
PC accessories	None					4		
	Serial interface cable for service use, DMT242RS				E	3		
Installation accessories	None					0		
	Basic sampling cell, DMT242SC					1		
	Sampling cell, swagelok 1/4" male connectors, DMT242SC2					2		
	Sampling cell with quick connector and leak screw, DSC74					3		
	Two pressure sampling cell, DSC74B					4		
	Two pressure sampling cell with coil, DSC74C					5		
	NPT 1/2" adapter					6		
Haarla quida	Duct installation flange DM240FA					9	,	
User's guide	None						A B	
	English German						С	
	French						D	
	Japanese						.1	
	σαγαποσο					TOT	ΔI	
						_	TY	
				TO	TAI	VAL		
				. 0	.,		[

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings: DMT242 A 1 D 1 A 0 B

End customer:		

Accessories:

226476 Loop-powered display 4...20 mA / -80....20 ℃ Tdf , Nokeval 301

POWER-1 100...240 VAC external power supply

DMT242RS Serial interface cable

