



Order form
Orderer

Valid from 3rd September 2007
Order no.

Vaisala CARBOCAP® Carbon Dioxide Probe GMP343

		Fill here										PRICE
Vaisala CARBOCAP® Carbon Dioxide Probe GMP343											0	
Sampling method	diffusion flow through	A	B									
Measurement range of the probe:	0...1000 ppm CO₂	1										
	0...2000 ppm CO₂	2										
	0...3000 ppm CO₂	3										
	0...4000 ppm CO₂	4										
	0...5000 ppm CO₂ *	5										
	0...2 % CO₂ *	6										
Analog output selection **	0...5 V	A										
	0...2.5 V	B										
	4...20 mA	C										
Digital output selection	RS232	1										
	RS485 ***	2										
Probe cable	none									N		
	<i>probe cable (with M12 type female connector), 2 m</i>									A		
	<i>probe cable (with M12 type female connector), 6 m</i>									B		
	<i>probe cable (with M12 type female connector), 10 m</i>									C		
Measurement indicator MI70 and accessories	none									0		
	<i>MI70 indicator and interface cable, 2 m ****</i>									1		
	<i>MI70 interface cable, 2 m</i>									2		
Calibration accessories	none									N		
	<i>calibration adapter for diffusion model</i>									A		
	<i>PC connection kit*****</i>									B		
	<i>calibration adapter for diffusion model and PC connection kit*****</i>									C		
Mounting accessories	none									0		
	<i>mounting flange</i>									1		
Wiring accessories	none									N		
	<i>junction box</i>									A		
User's Guide	no User's Guide										A	
	English										B	
	Japanese										J	
TOTAL												
QTY												
TOTAL VALUE												

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code:

GMP343	A	1	A	1	A	0	A	0	A	0	B
---------------	---	---	---	---	---	---	---	---	---	---	---

End customer: _____

Notes for the selections:

- * The ranges 0...5000 ppmCO₂ and 0...2 %CO₂ have reduces accuracy specifications above 4000 ppmCO₂
- ** The analog output type (current or voltage mode) may be selected and re-scaled using PC connection cable by customer
- *** If the selection is RS485, the device may be powered up in the RS232 service mode for user settings. See User's Guide for details.
- **** The selection includes:
 - MI70 indicator with a rechargeable battery
 - AC adapter with AUS, EUR, UK, and US plugs
 - MI70Link software with RS232 cable (PC <-> MI70)
 - 2 m interface cable (GMP343 <-> MI70)
- ***** The selection includes PC connection cable (213379) and USB adapter (USB-D9 Serial connection cable, 219686)

Note: following accessories are also available as a spare parts:

<u>ACCESSORY</u>	<u>CODE:</u>	<u>NOTE:</u>
Wall mount bracket	GMP343BRACKET	Included in the default configuration
Mounting flange	GMP343FLANGE	
Standard diffusion filter (IP65) + filter cover	GMP343FILTER	Included in the default configuration of diffusion model
Diffusion filter (sintered filter, IP66) + filter cover	215521	
Calibration adapter	GMP343ADAPTER	
Junction box	JUNCTIONBOX-8	
Probe cable (with M12 type female conn.), 2 m	GMP343Z200SP	
Probe cable (with M12 type female conn.), 6 m	GMP343Z600SP	
Probe cable (with M12 type female conn.), 10 m	GMP343Z1000SP	
PC connection cable	213379	
Interface cable for MI70, 2 m	DRW216050SP	
USB adapter (USB-D9 Serial connection cable)	219686	
Soil adapter kit for horizontal positioning	215519	Includes sintered PTFE filter
Soil adapter kit for vertical positioning	215520	Includes sintered PTFE filter