



Order form  
Purchaser

## Vaisala HUMICAP® Humidity and Temperature Transmitter HMD110

Vaisala HUMICAP® Humidity and Temperature transmitter						HMD110	2		V		PRICE
1 Output signals	<b>4 ...20 mA</b>						<b>2</b>				
2 Measured parameter for channel 1	<b>RH</b>						<b>A</b>				
	<b>Td</b>	<b>(-40 ... +60°C)</b>					<b>B</b>				
	<b>T</b>	<b>(-40 ... +60°C)</b>					<b>C</b>				
	<b>Tw</b>	<b>(-40 ... +60°C)</b>					<b>D</b>				
	<b>h</b>	<b>(-40 ... 460 kJ/kg)</b>					<b>H</b>				
	<i>Td, free scale scale</i>	<i>Low</i>	<i>High</i>	°C			X				
	<i>Tw, free scale scale</i>	<i>Low</i>	<i>High</i>	°C			Y				
	<i>h, free scale scale</i>	<i>Low</i>	<i>High</i>	kJ/kg			Z				
3 Measured parameter for channel 2	<b>Td</b>	<b>(-40 ... +60°C)</b>					<b>0</b>				
	<b>T</b>	<b>(-40 ... +60°C)</b>					<b>1</b>				
	<b>T</b>	<b>(-5 ... +55°C)</b>					<b>2</b>				
	<b>T</b>	<b>(0 ... +50°C)</b>					<b>3</b>				
	<i>T, free scale</i>	<i>Low</i>	<i>High</i>	°C			X				
4 Identity	<b>Vaisala</b>							<b>V</b>			
5 Humidity sensor	<b>Humicap180R</b>							<b>A</b>			
	<i>Catalytic humicap sensor</i>	<i>VHC180</i>						<b>C</b>			
6 User guide	<b>No user guide</b>									<b>0</b>	
	<b>Multilingual quick guide</b>									<b>1</b>	
TOTAL											
QTY											
TOTAL VALUE											

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.



**www.esis.com.au**  
Ph 02 9481 7420  
Fax 02 9481 7267  
esis.enq@esis.com.au

Industrial Electronics

Example of order code with typical settings:

HMD110	2	A	1	V	A	1
--------	---	---	---	---	---	---

