

Vaisala HUMICAP®

Moisture and Temperature Transmitter Series for Oil

MMT330



Know Your Oil Better

MMT330 Moisture and Temperature Transmitter Series for Oil



The MMT330 transmitter family offers a range of solutions for demanding moisture in oil measurements.

The Vaisala HUMICAP® Moisture and Temperature Transmitter Series for Oil MMT330 enables fast and reliable detection of moisture in oil. The MMT330 can be used in on-line moisture monitoring and as a control device, allowing separators and oil driers to be started only when needed.


Proper monitoring saves both oil and the environment. With the MMT330 it is easy and economical to monitor the effects of moisture in oil.

Reliable Vaisala HUMICAP® technology

The MMT330 incorporates the latest generation of the Vaisala HUMICAP® Sensor, which is the result of ten years of field experience. It was developed for demanding moisture measurement in liquid hydrocarbons. The sensor's excellent chemical tolerance provides accurate and reliable measurement over a wide measurement range.

For diverse applications and demanding conditions

Because of the variety of probes, the transmitter can be used in



The display shows measurement trends and up to one year in historical data.

lubrication systems, hydraulic systems, and transformers.

Indicates the margin to water saturation

The MMT330 measures moisture in oil in terms of the water activity (a_w) and temperature (T). Water activity indicates directly whether there is a risk of free water formation. The measurement is also independent of oil type and age.

Water content as ppm conversion

In addition to water activity, the MMT330 can output ppm, the average mass concentration of water in oil.

Features/Benefits

- Continuous on-line measurement of moisture in oil
- Ball valve installation
- no need to shut down the process
- Incorporates Vaisala HUMICAP® Sensor - more than 30 years of field performance
- Ten years of experience in measuring moisture in oil
- Excellent long-term stability
- Easy to calibrate and maintain in the field - Compatible with Vaisala HUMICAP® Hand-Held Moisture for Oil Meter MM70

Vaisala has this conversion readily available for mineral transformer oil. For other oils, the oil specific conversion coefficients can be programmed to the transmitter if the water solubility of the oil is known.

Graphical measurement trend and historical display

The MMT330 can be ordered with a large numerical and graphical display with a multilingual menu. It allows the user to monitor measurement trends over a 1-year history.

Versatile outputs

The MMT330 provides up to three analog outputs. Galvanic isolation of supply power and analog outputs is also available. For serial interface the RS232 and RS485 can be used. In addition, alarm relay option is available.

Easy installation


The MMT330 has several options for transmitter mounting. Transmitters are delivered pre-configured with all settings installation ready.



The MMT332 probe is installed using a flange. It is for high pressure applications.

MMT332 For High Pressure Installations


Pressure range	0..250 bar / 0..3625 psia
Probe diameter	12 mm / 0.5 inch
Installation	
Flange	36 mm / 1.4 inch
Temperature	
Measurement range	-40...+180 °C



The MMT337 probe, with optional Swagelok connector, is ideal for tight spaces with a thread connection. The small probe is designed for integrating into confined spaces with small diameter lines.

MMT337 with Small Sized Probe


Pressure range	0..10 bar / 0..145 psia
Probe diameter	12 mm / 0.5 inch
Installation	
Fitting Body	R 3/8" ISO
Fitting Body	NPT 1/2"
Temperature	
Measurement range	-40...+180 °C



The MMT338 is ideal for installations in pressurized processes where the probe needs to be removed while the process is running. The sensor head depth is adjustable.

MMT338 with Probe for Pipeline Installations

Pressure range	0..40 bar / 0..580 psia
Adjustable length	41..149/371 mm / 1.61..5.87/14.6 inch
Installation	
Fitting Body	R1/2" ISO
Fitting Body	NPT 1/2"
Ball Valve Set	BALLVALVE-1
Sampling Cell	DMT242SC2
Temperature	
Measurement range	-40...+180 °C



The Vaisala HUMICAP® Hand-Held Moisture for Oil Meter MM70 is designed for field checking MMT330 transmitters.



The MMT330 is often used for measuring moisture in transformer oil.

Technical Data

Measured values

Water activity	
Measurement range a_w	0...1
Accuracy (including nonlinearity, hysteresis and repeatability)	±0.02
0...0.9	±0.02
0.9...1.0	±0.03
Response time (90%) at +20 °C in still oil (with stainless steel filter)	10 min.
Sensor	HUMICAP®

Performance

Temperature	
Measurement range	
MMT332	-40...+180 °C
MMT337	-40...+180 °C
MMT338	-40...+180 °C
Accuracy at +20 °C (+68 °F)	± 0.2 °C

Operating environment

Operating temperature	
for probes	same as measurement ranges
for transmitter body	-40...+60 °C (-40...+140 °F)
with display	0...+60 °C (+32...+140 °F)
Pressure range for probes	See probe specifications

Complies with EMC standard
EN61326-1:1997 + Am1:1998 + Am2:2001; Industrial Environment

Inputs and outputs


Operating voltage	10...35 VDC, 24 VAC
with optional power supply module	100...240 VAC 50/60 Hz
Power consumption @ 20 °C (U_{in} 24VDC)	
RS-232	max 25 mA
U_{out} 2 x 0...1V / 0...5V / 0...10V	max 25 mA
I_{out} 2 x 0...20 mA	max 60 mA
display and backlight	+ 20 mA
Analog outputs (2 standard, 3rd optional)	
current output	0...20 mA, 4...20 mA
voltage output	0...1 V, 0...5 V, 0...10 V
Accuracy of analog outputs at 20 °C	± 0.05 % full scale
Temperature dependence of the analog outputs	± 0.005 %/°C full scale
External loads	
current outputs	$R_L < 500 \text{ ohm}$
0... 1V output	$R_L > 2 \text{ kohm}$
0... 5V and 0... 10V outputs	$R_L > 10 \text{ kohm}$
Max wire size	0.5 mm ² (AWG 20) stranded wires recommended
Digital outputs	RS-232, RS-485 (optional)
Relay outputs	0.5 A, 250 VAC, SPDT, Potential Free (optional)
Display	LCD with backlight, graphic trend display of any parameter
Display menu languages	English, French, Spanish, German, Japanese, Russian, Swedish, Finnish

Mechanics

Cable bushing	M20x1.5 for cable diameter 8...11mm/0.31...0.43"
Conduit fitting	1/2"NPT
Interface cable connector (optional)	M12 series 8 pin (male)
option 1	with plug (female) with 5 m / 16.4 ft black cable
option 2	with plug (female) with screw terminals

Probe cable diameter	5.5 mm
Probe cable lengths	2 m, 5 m or 10 m
Housing material	G-AlSi 10 Mg (DIN 1725)
Housing classification	IP 65 (NEMA 4X)

Mounting options



Mounting with
Wall Mounting Kit

Mounting with DIN Rail
Installation Kit




Pole Installation with
Installation Kit
for Pole or Pipeline

Mounting Rain Shield with
Installation Kit



Dimensions

Dimensions in mm (inches)



HUMICAP® is a registered trademark of Vaisala.
Specifications subject to change without prior notice.
©Vaisala Oyj

