

## CMB-67H-01

- Mini-ITX barebone system support 2<sup>nd</sup> generation Intel® Core™ i7 / i5 / i3 mobile processor
- Support one PCI-Express X16 slot , HD Audio
- VGA , DVI , 2 x Intel® Giga LAN , COM , USB



<b>Form Factor</b>	Mini-ITX Barebone system
<b>Construction</b>	Heavy-Duty steel
<b>Processor</b>	Support 2 <sup>nd</sup> generation Intel® Core™ i7 / i5 / i3 in PGA 988B
<b>Chipset</b>	Intel® QM67 Express Chipset
<b>Memory</b>	Two DDR3 1066/1333 SO-DIMM up to 16 GB
<b>Drive Bay</b>	one internal 3.5" HDD or 2 x internal 2.5" HDD space or two external 2.5" HDD space by drive cage
<b>Extensive slot</b>	One PCI-Express X16 slot. ( Not all the PCIe cards could be fitted duo to internal physical issue )
<b>System Fan</b>	One 6 cm system cooling Fan
<b>Front Panel</b>	Power on switch , LED for Power On/Off and HDD activity 2 x USB ports , Mic-in / Ear phone
<b>Rear Side I/O</b>	PS/2 Key/Mouse, 2 x RJ45 LAN, 4 x USB 2.0, 1 x RS232/422/485, 2 x RS232 1 x VGA, 1 x DVI, 1 x Audio, 1 x SPDIF Reserve 2 x DB9 COM port holes ( Can't be used when install 3.5" HDD or 2.5" external driver bay ))
<b>Power supply</b>	250 Watt ( AC 100 ~ 240V )
<b>Environment</b>	Operating Temperature: 0 ~ 40°C . Humidity: 10 ~ 85% @ 40°C (non-condensing)
<b>Dimension</b>	220 x 300 x 80 mm ( L x W x H )

### Ordering Code

<b>CMB-67H-01</b>	Barebone system with LV-67HTXD , CPU cooler Fan , 250 Watt power supply & 1 x PCIe riser card
<b>Processor</b>	Intel® Core™ i7-620M / i5-520M mobile processor
<b>Memory</b>	DDR3 1066/1333/1600 for 1.0 GB / 2.0 GB / 4.0 GB
<b>Drive cage</b>	Support External 2 bay 2.5" Mobile Rack