

CMB-67H-02

- Mini-ITX barebone system support 2nd generation Intel® Core™ i7 / i5 / i3 mobile processor ,HD Audio
- VGA , DVI , 2 x IntelR Giga LAN , COM , USB



Form Factor	Mini-ITX Barebone system
Construction	Heavy-Duty steel
Processor	Support 2 nd generation Intel® Core™ i7 / i5 / i3 in PGA 988B
Chipset	Intel® QM67 Express Chipset
Memory	Two DDR3 1066/1333 SO-DIMM up to 16 GB
Drive Bay	One internal 1 x 2.5" HDD space and 1 x Slim CD-ROM Space
Extensive slot	Two Mini-PCIe sockets
System Fan	One 6 cm system cooling Fan
Front Panel	Power on switch , LED for Power On/Off and HDD activity , Reset switch 2 x USB ports , Mic-in / Ear phone
Rear Side I/O	PS/2 Key/Mouse, 2 x RJ45 LAN, 4 x USB 2.0, 1 x RS232/422/485, 2 x RS232 1 x VGA, 1 x DVI, 1 x Audio, 1 x SPDIF Reserve 2 x DB9 COM port holes
Power supply	19V/ 120W adapter
Environment	Operating Temperature: 0 ~ 40°C . Humidity: 10 ~ 85% @ 40°C (non-condensing)
Dimension	199 x 189 x 110 mm (L x W x H)

Ordering Code

CMB-67H-02	Barebone system with LV-67HTXD , CPU cooler Fan ,19V/ 120W adapter
Processor	Intel® Core™ i7-2710QE / i5-2510E / i3-2330E mobile processor
Memory	DDR3 1066/1333/1600 for 1.0 GB / 2.0 GB / 4.0 GB / 8.0 GB