



System

CPU	AMD 2nd Generation R-series APU on board, up to 2.7GHz
System Memory	2x DDR3 SO-DIMM, Max. 32GB
System Chipset	AMD A77E FCH
BIOS	AMI
Watchdog Timer	256 levels
SSD	1x mSATA
H/W Monitor	Yes
Expansion Slot	1x PCI-E (X16), 2x Mini PCI-E

Graphics

VGA Controller	AMD A77E built-in Radeon HD9000 series graphics core
VGA Memory	Shared memory
Display Interface	DVI-I, DisplayPort & 24-bit dual channel LVDS

LAN

Controller	3x Realtek 8111G Gigabit LAN
Connector	RJ-45 on board

Multi I/O

I/O Chipset	Fintek F81866AD-I 1x RS232/422/485(jumperless selection) 5x RS232, 5x SATA III (6.0Gb/sec.)
USB	4 ports (USB 3.0) + 2 ports (USB 2.0) on board 6 ports via pin header (USB 2.0)
Audio	Built-in HD audio w/ ALC662 codec for 5.1 channel
Others	Digital I/O (4-in/4-out), RAID, iSMART, SIM card slot

Features

- Supports AMD 2nd Generation R-series APU on board, up to 2.7GHz
- 2x DDR3 SO-DIMM, Max. 32GB
- 3x PCI-E Gigabit LAN
- DVI-I, DisplayPort & 24-bit dual channel LVDS
- Watchdog timer, Digital I/O, iSMART, RAID
- 5x SATA III, 4x USB 3.0, 8x USB 2.0, 6x COM, 1x mSATA
- 1x PCI-E(x16), 2x Mini PCI-E
- 1x SIM card slot

Mechanical and Environmental

Dimensions	170mm x 170mm (6.7" x 6.7")
Max. Power Requirement	AMD RX427 APU 2.70GHz 2GB DDR3-1333 +3.3V: 1.02A +5V: 1.88A +12V: 1.08A
Operating Temperature	0°C~60°C (32°F~140°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	90% (non-condensing @60°C)

Ordering Information

MI977F-Q27	AMD RX-427BB APU on board + A77E 2.7GHz Mini-ITX motherboard w/ DVI-I + DP & LVDS, triple Gigabit LAN, iSMART 3.1, RAID
MI977F-Q25	AMD RX-425BB APU on board + A77E 2.5GHz Mini-ITX motherboard w/ DVI-I + DP & LVDS, triple Gigabit LAN, iSMART 3.1, RAID
MI977F-D22	AMD RX-225FB APU on board + A77E 2.2GHz Mini-ITX motherboard w/ DVI-I + DP & LVDS, triple Gigabit LAN, iSMART 3.1, RAID

Dimensions and Drawing

