

UNO-2372G

Intel Atom Small-Size Modular Box Platform with 2 GbE, 4 USB, 4 COM, 2 mPCIe, HDMI, DP

NEW



UNO-2372G-E021AE

UNO-2372G-E022AE



Features

- Intel Atom Baytrial E3845 Quad-Core Processors up to 1.91GHz with 4G DDR3L Memory
- Robust and cableless design with high stability
- 2 x GbE, 4 x USB, 4 x RS-232/422/485, 1 x HDMI, 1 x DP
- Modular design with flexibility to extend second stack for function enhancement
- Compact size with fanless Design
- Rubber stopper design for stand mount and optional kit for DIN-rail mount, and VESA mount
- Optional 3G/GPS/GPRS/Wi-Fi Communication

Introduction

Advantech's new generation UNO-2000 series of Embedded Automation Computers are highly ruggedized fanless and modular design. The incredible modularity of UNO-2372G offers numerous performance and cost-saving advantages, including elimination of unnecessary features and expenses, accelerated production and delivery, rapid deployment and integration, reduced system downtime and maintenance costs, and support for future upgrades and expansion. The UNO-2372G's modular design features optimized I/O and an optional second expansion stack that support Advantech's iDoor technology. This allows the platform functionalities to be easily extended and customized with the integration of various iDoor modules, including industrial Fieldbus, wireless communication, I/O and peripheral module, to provide purpose-built, future-proof solutions that satisfy specific application requirements.

Specifications

General

- Certification** CE, FCC, UL, CCC, BSMI
- Dimensions (W x D x H)** 150 x 105 x 35mm (5.8" x 4.2" x 1.4")
- Form Factor** Small Size
- Enclosure** Aluminum Housing
- Mounting** Stand, Wall, VESA (Optional)
- Weight (Net)** 1.0kg (2.2lbs)
- Power Requirement** 10 - 36V_{dc}
- Power Consumption** 14W (Typical), 42W (Max)
- OS Support** Microsoft® Windows 7, Windows 10, Advantech Linux

System Hardware

- BIOS** AMI UEFI64 Mbit
- Watchdog Timer** Programmable 255 levels timer interval, from 1 to 255 sec
- Processor** Intel Atom Quad Core E3845 1.91GHz
- Memory** Built-in 4GB DDR3L 1600MHz
- Graphics Engine** Intel HD Graphics
- Ethernet** Intel® i210-IT GbE, 802.1Qav, 802.1AS, 802.3az
- LED Indicators** LEDs for Power, RTC battery, LAN (Active, Status) and HDD
- Storage** 1 x mSATA slot
1 x drive bay for SATA 2.5" HDD (Compatible with 9.5mm height HDD)
- Expansion** 2 x Full size mPCIe slots (one default setting on mSATA, one default setting on mPCIe)

I/O Interfaces


- Serial Ports** 4 x RS232/422/485, DB9, 50 ~ 115.2kbps
- LAN Ports** 2 x RJ45, 10/100/1000 Mbps IEEE 802.3u 1000Base-T Fast Ethernet
- USB Ports** 1 x USB 3.0, 3 x USB 2.0 Compliant
- Displays** 1 x DisplayPort 1.2, supports 2560x1440p @60Hz
1 x HDMI v1.4, supports 1920x1080p @60Hz
- Power Connector** 1 x 2 Pins, Terminal Block

Environment


- Operating Temperature** -20 ~ 60°C (-4 ~ 140°F) @ 5 ~ 85% RH with 0.7m/s airflow
- Storage Temperature** -40 ~ 85°C (-40 ~ 185°F)
- Relative Humidity** 10 ~ 95% RH @ 40°C, non-condensing
- Shock Protection** Operating, IEC 60068-2-27, 50G, half sine, 11ms
- Vibration Protection** Operating, IEC 60068-2-64, 2Grms, random, 5 ~ 500Hz, 1hr/axis (mSATA)
Operating, IEC 60068-2-64, 0.75Grms, random, 5 ~ 500Hz, 1hr/axis (HDD)
- Ingress Protection** IP40

Installation Scenario

DIN-rail Mount Illustration



VESA Mount Illustration



Ordering Information

- UNO-2372G-E021AE** Intel Atom E3845 1.91GHz, 4GB, 2 x GbE, 2 x mPCIe, HDMI/DP
- UNO-2372G-E022AE** Intel Atom E3845 1.91GHz, 4GB, 2 x GbE, 2 x mPCIe, HDMI/DP, with 2 stacks chassis for iDOOR expansion

