### **thermo**scientific







# Thermo Scientific™ Eutech™ Expert pH & Expert CTS Testers

Main Features

- User friendly One year warranty Large 4 digit double line display
- Simultaneous temperature display Battery life, ready & calibration indicators
- Automatic temperature compensation Auto pH buffer recognition & calibration



Lanyard provision enables easy transport for on-the-go measurement



Easy battery replacement - No special tools required



Pocket tester floats & meets waterproof IP67 rating



Cap secures to the top of the tester when not in use



Wide, stable base allows the tester to stand independently



www.esis.com.au Ph 02 9481 7420 Fax 02 9481 7267 esis.enq@esis.com.au



#### Display:

- Large 4 digit double line display and wide viewing angle make it easy to read and record measurements
- Battery life, ready, and calibration indicators simplify measurement and pocket tester maintenance
- Simultaneous display of temperature; user selectable °C or °F

#### Keypad:

- Easy to operate and intuitive user interface with power, calibration, menu and enter keys
- One push calibration: Immerse sensor in calibration solution and press "Cal"
- Auto pH buffer recognition and calibration

#### Cap:

- Gasketed o-ring seal on Eutech Expert pH tester prevents leaks during measurement and storage
- Transparent cap with a fill line indicator for measurement and calibration – no beakers or sample cups needed
- New symmetrical cap can face forward or backward

#### **Additional Features:**

- Automatic Temperature Compensation for greater accuracy
- Auto off function after 8.5 minutes of non-use to extend battery life
- Multi-language instructions available
- Acrylonitrile Butadiene \$tyrene (ABS) plastic body is durable and chemically resistant















### Thermo Scientific<sup>™</sup> Eutech<sup>™</sup> Expert pH Testers

### pH/Temperature

Simultaneously measure pH and temperature with the Thermo Scientific Eutech Expert pH testers, a pocket sized tester designed to provide accurate measurements on the go for a variety of applications, including hydroponic gardening, aquaculture, agriculture, pools, lab work, and other water applications.

- Auto-buffer recognition and auto-calibration make on-site calibration quick and easy
- 3-point calibration allows the tester to accurately measure pH across the acid and alkali ranges
- ±0.1% accuracy

**Applications:** • Hydroponics • Agriculture • Aquaculture & Aquariums • Pools & Spas • Education • Cooling Towers

 Water Treatment
 Environmental Monitoring
 Food & Beverage Manufacturing • Printing and more!



www.esis.com.au Ph 02 9481 7420

Specifications					
Measuring Pa	arameter	pH/°C/°F			
	Range	0.0 to 14.0 pH			
рН	Resolution	0.1 pH			
	Relative Accuracy	±0.1 pH			
No. of Cal Points		1 to 3 points			
	Range	0 to 50.0 °C			
		32.0 to 122.0 °F			
	Resolution	0.1 °C / 0.1 °F			
Tomporaturo	Relative Accuracy	±0.5 °C / ±0.9 °F			
remperature		+1 LSD			
	Automatic				
	Temp.	Yes			
	Compensation				
	Power	Includes (4) batteries			
		(A76 or LR44 equivalent)			
	Auto Off	8.5 mins after last key press			
General	Operating Temp.	5 to 45 °C			
	Ingress Protection	IP67 rating; waterproof			
	Dimensions	17 x 4.5 x 3 cm			

	Ordering Information			
	Order Code	Product Description		
	Pocket Tester			
	EXPERTPH	Expert pH pocket tester, batteries		
	pH Buffer Solutions			
	ECBU4BT	Colourless pH 4.01, 480 mL		
	ECBU7BT	Colourless pH 7.00, 480 mL		
	ECBU10BT	Colourless pH 10.01, 480 mL		
	ECPHBUFKIT	Colourless pH buffer set,		
		pH 4.01, 7.00, 10.01, 480 mL each		
	pH Buffer Sachets			
	ECBU4BS	pH 4.01 (NIST traceable),		
	2000 100	box of 20 x 20 mL sachets		
	ECBU7BS	pH 7.00 (NIST traceable),		
		box of 20 x 20 mL sachets		
	ECBU10BS	pH 10.01 (NIST traceable),		
		box of 20 x 20 mL sachets		
	ECRINWT	pH deionized water (NIST traceable),		
		box of 20 x 20 mL sachets		
	ECBU4710R	pH buffer sachet set, pH 4.01, 7.00, 10.01,		
	deionized water, 5 x 20 mL each			
	Storage & Cleaning Solutions			
	ECRE005	Storage solution for pH sensor, 480 mL		
	ECDPCBT	Protein remover solution, 480 mL		
	Accessories			
	EXPERTCAP	Replacement clear cap for samples & storage		



(LxWxH)

## **thermo**scientific

### Thermo Scientific™ Eutech™ Expert CTS Testers

Conductivity/TDS/Salinity/Temperature

The Thermo Scientific Eutech Expert CTS tester accurately measures conductivity, TDS, and salinity in one single instrument, making it an ideal solution for many applications.

**Applications:** • Hydroponics • Agriculture • Aquaculture & Aquariums • Pools & Spas • Education • Cooling Towers • Water Treatment • Environmental Monitoring • Food & Beverage Manufacturing • Printing and more!

Specifications					
Measuring Pa	ırameter	Conductivity / TDS / Salinity / °C / °F			
	Range	0.00 to 20.00 mS/cm			
Conductivity	Resolution	10 μS/cm below 2.00 mS/cm, 0.10 mS/cm above 2.00 mS/cm			
Conductivity	Relative Accuracy	±2 % full scale ±1 LSD			
	Automatic Calibration Values	84 μS/cm, 1413 μS/cm, 12.88 mS/cm			
	Range	0.00 to 20.00 ppt			
TDS	Resolution	10 ppm below 2.00 ppt, 0.10 ppt above 2.00 ppt			
	Relative Accuracy	±2 % full scale ±1 LSD			
	TDS Factor	0.40 to 1.00 (selectable)			
	Range	0.0 to 10.0 ppt			
Salinity	Resolution	0.10 ppt			
	Relative Accuracy	±2 % of full scale ±1 LSD			
No. of Cal Po	ints	One calibration point per parameter			
	Range	0 to 50.0 °C; 32.0 to 122.0 °F			
	Resolution	0.1 °C / 0.1 °F			
Temperature	Relative Accuracy	±0.5 °C / ±0.9 °F + 1 LSD			
	Automatic Temp. Compensation	Yes			
	Power	Includes (4) batteries (A76 or LR44 equivalent)			
General	Auto Off	8.5 mins after last key press			
General	Operating Temp.	5 to 45 °C			
	Ingress Protection	IP67 rating; waterproof			
	Dimensions (LxWxH)	17 x 4.5 x 3 cm			



ECCON1413BT 1413 μS/cm KCl, 480 mL ECCON1288BT 12.88 mS/cm KCl, 480 mL

**TDS 442 Standard Solutions** 

Salinity (NaCl) Standard Solutions

EC442300BT

EC4421000BT

EC4423000BT

**ECNACL5PPT** 

**Accessories** EXPERTCAP

ECCON1413BS 1413 μS/cm KCl, box of 20 x 20 mL sachets

300 ppm 442, 480 mL

1000 ppm 442, 480 mL

3000 ppm 442, 480 mL

Replacement clear cap for samples & storage

5 ppt NaCl, 480 mL



