



Valid from 20130826 JAH Order Form

Vaisala Ultrasonic Wind Sensor WMT700

	MAT TO		1				ı		1		1		1	
1	WMT 7 0 Measurement range			1	1									
•	65 m/s WMT702	2												
	65 m/s + Accredited Wind Calibration (WMT702)	В												
2	Temperature range		^											
	-10+60 C -40+60 C		A B											
	-55+70 C		Č											
3	Heating			_										
	Non-heated version			1										
	Heated transducers			2 3										
	Heated transducers and arms Heated transducers, arms and body			3 4										
4	Digital communication interface													
	RS-485 isolated				Α									
	RS-422 isolated RS-232 isolated				B C									
	SDI-12 isolated				D									
5	Digital communication profile													
	WMT70 - poll mode (default)	9600b, 8, N, 1 Pol				0								
	WS425 - ASCII	2400b, 8, N, 1 Pol				1								
	WS425 - NMEA Extended (v 0183) WS425 - SDI-12 (v 1.3)	9600b, 8, N, 1 Aut 1200b, 7, E, 1 Poll				2 3								
	WS425 - ASOS	2400b, 8, N, 1 Pol				4								
	ROSA - MES12	9600b, 8, N, 1 Pol	lled			5								
6	AWS520 - NMEA Extended (v 0183)	4800b, 8, N, 1 Aut	to send 1/s			8	l							
6	Digital communication units m/s						Α							
	knots						В							
	mph						С							
7	km/h						D							
7	Analog output signals for wind speed channel Disabled							0						
	Voltage output	100 mV/m/s						1						
	Current output	420 mA	(0Range	e m/s)				3						
	Current output	0.2 mA/m/s						4						
	Push-Pull frequency output	10 Hz/m/s 8 mV/mph						6 7						
	WS425 - voltage output WS425 - frequency output (Push-Pull)	5 Hz/mph						8						
	Pull up frequency output (PNP)	10 Hz/m/s						Ä						
	Pull down frequency output (NPN)	10 Hz/m/s						В]					
8	Analog output signals for wind direction channel Disabled								0					
	Voltage output	20 mV/Deg							A					
	Current output	50 uA/Deg							D					
	Current output 420 mA	44.444 uA/Deg							E					
9	Potentiometer output (WS425) Cable	0Vref (Vref = ext	ternal refer	ence voltag	e from syste	m)			F					
9	None									1				
	Cable 2 m, cable connector, open leads on one e	end								2				
	Cable 10 m, cable connector, open leads on one	end								3				
	MAWS cable 10 m AWS520 cable 10 m, shield connected to PE pin									4 5				
	Adapter cable for WS425 serial									6			1	
	Adapter cable for WS425 analog frequency outp									7				
	RS485 Cable 2 m, cable connector, open leads of									8				
	RS485 Cable 10 m, cable connector, open leads Adapter cable for WS425 analog voltage output	on one end								9 A				
	AWS520 cable 10 m, shield not connected to PE	pin								В				
	ROSA analog cable 10 m, cable connector, oper									С				
	Junction Box with Cable 2meters									D				
	Cable 15 m, cable connector, open leads on one Cable 26 m, cable connector, open leads on one									E F				
10	Mounting adapter	cnd								- 1				
-	Adapter 228869 only Standard adapter, no fix									Α		1		
	Adapter 228869 with WMT70FIX70 (suitable also	for inverted mounting	ng)				general pur				В		1	
	Adapter 228869 with WMT700FIX60-POM Adapter 228869 with WMT700FIX60-RST						plastic fix for stainless st				С			
	Adapter 228869 with WM 1700FIX60-RS I Adapter 228777 only (used for old WS425 FIX30	/60)					stainless st apter, no fix		o mm poie		D E			
11	Power - Reserved for furture purposes	100)			W0420 00	inpatible ad	aptor, no na							
	None											1	J	
12	Accessories												Α.	
	None Bird cage												A B	
													ь	ı
13	Manual													
13	None													1
13	None English													2
13	None English Japanese													2
13	None English													2

For freezing conditions select appropriate combination of heating and temperature ranges.

Accessor	ies		
	Tool	Verifier Cable Tightener Tool	WMT70Verifier 237888SP
	B: 1	·	MATTER 1100
	Bird	Bird cage Bird perch	WMT70BirdKit WS425BirdPerch
		Bild percil	W3423BildFelCil
	Cable	Cable connector	WMT70Conn
		Cable 2 m, cable connector, open leads on one end	227567SP
		Cable 10 m, cable connector, open leads on one end	227568SP
		Cable 15 m, cable connector, open leads on one end	237890SP
		Cable 26 m, cable connector, open leads on one end	237889SP
		RS485 Cable 2 m, cable connector, open leads on one end	228259SP
		RS485 Cable 10 m, cable connector, open leads on one end	228260SP
		MAWS cable 10 m	227565SP
		AWS520 cable 10 m, shield connected to PE pin	229807SP
		AWS520 cable 10 m, shield not connected to PE pin	227566SP
		ROSA analog cable 10 m, cable connector, open leads on one end	231425SP
		Adapter cable for WS425 serial	227569SP
		Adapter cable for WS425 analog frequency output	227570SP
		Adapter cable for WS425 analog voltage output	227571SP
		Junction Box with Cable 2meters	ASM210719SP
	Mounting	WMT700 Mounting Accessories:	
		Adapter for FIX70	228869
		Fix70 (suitable also for inverted mounting)	WMT70FixSP
		Mounting adapter 60mm POM	WMT700FIX60-POM
		Mounting adapter 60mm RST	WMT700FIX60-RST
		Cross-arm (40x40x850mm)	WMT70CROSSARM
		WS425 Mounting Accessories:	
		Adapter for old WS425 FIX30/60	228777
		FIX30	WS425Fix30
		FIX60	WS425Fix60
		Sensor support arm for 60mm pole (655mm with integrated fix for item 228777)	WAC425