

RK500-04 Dissolved Oxygen(DO) Sensor design based on the principle of fluorescence and high performance through oxygen membrane, with short response time, measurement accuracy, stable performance, etc.It can be widely used in chemical fertilizer, metallurgy, environmental protection water treatment engineering, pharmaceutical, biochemical, food, aquaculture and water such as continuous monitoring of dissolved oxygen in the solution.

FEATURES

- On-line & real-time monitoring
- With temperature compensation
- High accuracy
- Simple operation and high reliability
- No external module, a whole design
- Long service life
- Dissolved oxygen and temperature measurement at the same time(RS485)
- No requirement for liquid velocity
- Not affected by ions



APPLICATIONS

- Environmental protection
- Water quality monitoring
- Aquaculture
- Clean in place(CIP)
- Sewage treatment
- Industrial wastewater treatment

TECHNICAL SPECIFICATION

Item	Technical Specification	
	DO	Temperature
Range	0-20mg/L(ppm)	0-60℃
Accuracy	±0.5%FS	±0.5℃
Resolution	0.01mg/L	0.1℃
Supply	12VDC,24VDC	
Temperature compensation	0-60℃	
Output	RS485	
Measuring principle	Fluorescence	
Maintenance	Every 1year to replace fluorescent cap	
Response time	<60s	
Pressure Resistance	0.3MPa	
Power consumption	<0.4W	
Operating Temperature	0-+80℃	

RK500-04 Dissolved Oxygen Sensor



www.rikasensor.com.cn

Probe material	General: 316L For seawater: titanium alloy
Dimension	Φ 16*125mm
Weight(probe)	1.5kg
Ingress Protection	IP68
Storage	10-60℃@20%-90%RH
Cable length	10m default, other length customizable



Complies with applicable CE directives.

Specifications subject to change without notice. Version 3.0

Copyright © 2015 Hunan Rika Electronic Technology Co.,Ltd

Hunan Rika Electronic Technology Co., Ltd

Add:No 499# of Yingxin Road,
Yuhua District,Changsha,
Hunan,China



+86-731-85132979



info@rikasensor.com



www.rikasensor.com.cn

 Industrial Electronics	www.esis.com.au
	Ph 02 9481 7420
	Fax 02 9481 7267
	esis.enq@esis.com.au