

VAISALA

Order form
Orderer

Valid from 7 March 2013
Order no.

Vaisala CARBOCAP® Carbon Dioxide Probe GMP343

		Fill here										PRICE
Vaisala CARBOCAP® Carbon Dioxide Probe	GMP343										0	
Sampling method	diffusion <i>flow through</i>	A										
Measurement range of the probe:	0...1000 ppm CO ₂	1										
	0...2000 ppm CO ₂	2										
	0...3000 ppm CO ₂	3										
	0...4000 ppm CO ₂	4										
	0...5000 ppm CO ₂	5										
	0...2 % CO ₂ *	6										
Analog output selection **	0...5 V	A										
	0...2.5 V	B										
	4...20 mA	C										
Digital output selection	RS232	1										
	RS485 ***	2										
Probe cable	none	N										
	<i>probe cable (with M12 type female connector), 2 m</i>	A										
	<i>probe cable (with M12 type female connector), 6 m</i>	B										
	<i>probe cable (with M12 type female connector), 10 m</i>	C										
Measurement indicator MI70 and accessories	none	0										
	<i>MI70 indicator and interface cable, 2 m ****</i>	1										
	<i>MI70 interface cable, 2 m</i>	2										
Calibration accessories	none	N										
	<i>calibration adapter for diffusion model</i>	A										
	<i>PC connection kit*****</i>	B										
	<i>calibration adapter for diffusion model and PC connection kit*****</i>	C										
Mounting accessories	none	0										
	<i>mounting flange</i>	1										
Wiring accessories	none	N										
	<i>junction box</i>	A										
Special features	none	0										
User's Guide	no User's Guide	A										
	English	B										
	Japanese	J										
											TOTAL	
											QTY	
											TOTAL VALUE	

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code:

GMP343	A	1	A	1	A	0	A	0	A	0	A
--------	---	---	---	---	---	---	---	---	---	---	---

End customer: _____

Notes for the selections:

* Accuracy below 200 ppmCO₂ not specified for the 2% range option

** The analog output type (current or voltage mode) may be selected and re-scaled using PC connection cable by customer

*** If the selection is RS485, the device may be powered up in the RS232 service mode for user settings. See User's Guide for details.

**** The selection includes:

- MI70 indicator with a rechargeable battery
- AC adapter with AUS, EUR, UK, and US plugs
- MI70Link software with RS232 cable (PC <-> MI70)
- 2 m interface cable (GMP343 <-> MI70)

***** The selection includes PC connection cable (213379) and USB adapter (USB-D9 Serial connection cable, 219686)

Note: following accessories are also available as a spare parts:

ACCESSORY

Wall mount bracket
 Mounting flange
 Standard diffusion filter (IP65) + filter cover
 Diffusion filter (sintered filter, IP66) + filter cover
 Calibration adapter
 Junction box
 Probe cable (with M12 type female conn.), 2 m
 Probe cable (with M12 type female conn.), 6 m
 Probe cable (with M12 type female conn.), 10 m
 PC connection cable
 Interface cable for MI70, 2 m
 USB adapter (USB-D9 Serial connection cable)
 Soil adapter kit for horizontal positioning
 Soil adapter kit for vertical positioning

CODE:

GMP343BRACKET
 GMP343FLANGE
 GMP343FILTER
 215521
 GMP343ADAPTER
 JUNCTIONBOX-8
 GMP343Z200SP
 GMP343Z600SP
 GMP343Z1000SP
 213379
 DRW216050SP
 219686
 215519
 215520

NOTE:

Included in the default configuration
 Included in the default configuration of diffusion model
 Includes sintered PTFE filter
 Includes sintered PTFE filter