# PCIE-1680 PCI-1680U

## 2-Port CAN Bus PCIE Card with Isolation Protection

## 2-Port CAN Bus Universal PCI Card with Isolation Protection



#### **Features**

- PCle bus specification 1.1 compliant
- 2 x Independent CAN ports
- Up to 1 Mbps transmission speeds
- 16 MHz CAN controller frequency
- Optical isolation protection of 2,500 Vpc
- I/O address automatically assigned by PCI PnP
- Transmit/Receive status LED indicators
- Windows DLL library and examples included
- Supports Windows CE5/CE6/XP/7/8.1/10 drivers and utilities
- Supports Linux 2.4.xx/2.6.xx, QNX 6.5, and Intel<sup>®</sup> x86 architecture

### Introduction

PCI-1680 and PCIE-1680 are purpose-built communication cards that ensure CAN connectivity. With 2 independent CAN controllers built in, PCI-1680 and PCIE-1680 enable bus arbitration and error detection with automatic transmission repetition, drastically reducing data loss and ensuring system reliability. Additionally, both PCI-1680 and PCIE-1680 operate at baud rates of up to 1 Mbps.

### **Specifications**

#### General

Bus Type
PCI Express V1.0/Universal PCI

Certification CE, FCCConnectors 2 x DB9, male

2 x 10 pin box wafer (optional)

• Ports 2

■ Power Consumption 3.3 V @ 600 mA (typical)

#### Communication

CAN Controller
CAN Transceiver
Signal Support
Protocol
NXP SJA-1000
NXP TJA1051T
CAN\_H, CAN\_L
CAN 2.0 A/B

Data Transfer Rate
Programmable up to 1 Mbps

• CAN Frequency 16MHz

#### **Protection**

• Isolation Protection  $2,500 V_{DC}$ 

#### **Mechanical and Environmental**

■ Operating Temperature 0 ~ 70 °C (32 ~ 158 °F) (refer to IEC 60068-2-1, 2)

• Storage Temperature  $-40 \sim 85$  °C  $(-40 \sim 185$  °F)

• **Operating Humidity** 5 ~ 95% relative humidity, non-condensing

**Dimensions (L x H)** 168 x 111 mm (6.6" x 4.4")

## **Ordering Information**

PCIE-1680-AE
PCI-1680U-BE
2-port CAN bus PCIE card with isolation protection
2-port CAN bus PCI card with isolation protection

#### **Accessories**

OPT1-DB9E-AE DB9 to 10-pin wiring board

