

Nautilus High Temperature

Single-Channel Temperature Data Logger (Max 125°C)

The high temperature capabilities of the Nautilus High Temperature make it the ideal logger for monitoring temperature in extreme environments or environments where conventional data loggers are not able to

APPLICATIONS

Autoclave verification; ETO sterilization; kiln drying studies; medical & pharmaceutical studies; agricultrual, ocean and pond studies; environmental studies; process monitoring; HVAC; well monitoring; and hostile environmental monitoring.

GENERAL SPECIFICATIONS

Size: 18mm x 127mm (0.71" x 5.00")

Aluminum 51 g (1.8 oz); Stainless Steel 112 g (4 oz) Weight:

Case Material: Anodized Aluminum or Stainless Steel 3.6 volt Lithium, 0.95 Amp-Hour Battery:

Resolution: 8-bit (1 part in 256) Mounting: Locking hole on cap Clock Accuracy: ± 2 seconds per day

Sampling Methods: Continuous (First-in First-out), Stop When Full, Delay Start, or Spot & Average

10 to 125°C (50 to 257°F) and waterproof Operating Limits:

Windows PC with at least one free USB or serial port (depending on PC Requirements:

interface)

TrendReader® Express or TrendReader® (Compatible with Windows 7, 8 and 10) Software Requirements:

Memory Size: 32 KB (capable of storing up to 244,800 with data compression enabled)

Sampling Rates: User selectable rates from 8 seconds to 34 minutes (readings stored to memory

can be spot or averaged over the sample interval, except for the 8 second interval)

Number of Channels: One (one channel for ambient temperature)

SENSOR SPECIFICATIONS

NTC Thermistor - 100,000 Ohms @ 25°C (77°F) Temperature Sensor Type:

10°C to 125°C (50°F to 257°F) Range:

 10° C to 38° C (50° F to 100.4° F) better than $\pm 2.3^{\circ}$ C (4.14° F) System Accuracy:

 38° C to 121° C (101° F to 249° F) better than $\pm 1.2^{\circ}$ C (2.16° F) 121°C to 125°C (250°F to 257°F) better than ± 1.5 °C (2.7°F)

ORDERING INFORMATION

Cat#: NTL-102 (Aluminum) 01-0263 NTL-103 (Stainless Steel) 01-0264



www.esis.com.au Ph 02 9481 7420

Fax 02 9481 7267 esis.enq@esis.com.au



ACR Systems Inc Toll-Free: 1.800.663.7845 Tel: 1.604.591.1128 sales@acrsystems.com



ISO 9001 Certified

ISO9000\SPECIFICATIONS\NAUTILUS135.pdf



