



Features


- Widescreen 21.5" TFT LCD display, LED Backlit, Full HD 1920 * 1080;
- Intel 8th -gen. Whiskey Lake Celeron, Core i3/i5/i7 processor;
- Multi-point projected capacitive touch, or 5-wire resistive touch;
- Aluminum-magnesium alloy, anodized treatment, Modular designed;
- DC 12V, optional wide voltage DC 9~36V power input;
- IO: 2*GLAN, 4*USB3.0, 3*COM (DB9), 2*HDMI;
- Intel PTT TPM2.0, Support Windows 11 OS;
- Fan-less & Slim design, Panel mount, VESA, Front IP65 protection.



Specification

Hardware & System	BIOS	SPI AMI EEI BIOS
	CPU	Intel 8 th -gen. Whiskey Lake Celeron 4205U, Core i3-8145U, Core i5-8265U, Core i7-8565U
	Memory	SO-DIMM, DDR4-1866/2133/2400 MT/s, Max. up to 16GB
	Storage	1* M.2 NGFF Key-M/B slot + 1* 2.5" SATA
	Graphic	Intel UHD Graphics 620
	Network	1* Intel I211AT, and 1* Intel I219V LAN chips (Optional wireless 3G/4G, 5G, Wi-Fi/BT, Wi-Fi 6)
	Audio	On-board Realtek ACL 662 audio controller (Optional Line-Out connector available)
	Expansion	1* M.2 Key-B slot, 1* M.2 Key-E slot
	Watch dog	0~256 seconds programmable
	OS	Win10, Win11, Linux, Ubuntu
IO interface	COM	3*RS232 (Default), Optional 1* RS485 or 8*GPIO
	Ethernet	2* RJ45, 10/100/1000 Mbps
	Audio	Optional Line-out
	USB	4x USB3.0
	Display	2x HDMI
	Power	1x 2 pins, phenix terminal
LCD Display	Size/Type	21.5" TFT LCD
	Resolution	1920 * 1080 (Full HD)
	Brightness	250 nits
	Backlit & MTBF	LED backlit & 30 000hours
	Display area	476.64 * 268.11
	View angle	89/89/89/89
Touchscreen	Type	Projective capacitive touchscreen / Wide temp. 5-wires Resistive touchscreen, EETI controller
	Touch points	Multi points touch, max. up to 10 points (PCap) / Single touch (Resistive)
	Durability	>100 000 000 times (PCap) / 35 milion clicks@ 250g (Resistive)
	Surface hardness	Glass, Mohs 6H hardness (PCap) / PET film laminated, flat design (Resistive)
	Special treatment	Anti-fingerprint (PCap)
Structure	Structure and surface	Magnesium-Aluminum alloy, sand blasting, anodized treatment
	Mount method	Panel mount, VESA 75/100
	Cooling system	Large area finned heat sink
	Overall dimension	527 * 318.7 * 57.5 (mm)
	Cut-out dimension	516 * 308 (mm)
	Net weight	7.0 KG
	IP protection	Front Panel IP65
Power & Environmental	Operating temp.	0 ~ +60°C
	Storage temp.	-20 ~ +70°C
	Relative Humidity	10 ~ 95% @ 10C (Non-condensation)
	Vibration	50 ~ 500 Hz, 1.5G, 0.15mm peak to peak
	Shock	10G/Peak (11 ms)
	Power input	DC 12V (Optional DC 9~36V)
	Power consumption	Around 45W
	EMC	CE/FCC Class A

Dimensions (mm)



Ordering info.

Part no.	Description
PPC-DS215-W0-CT	21.5", 1920 * 1080, Celeron 4205U, Dual-core 1.8Ghz, Pcap. touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W1-CT	21.5", 1920 * 1080, Core i3-8145U, Dual-core 2.1Ghz, Pcap. touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W2-CT	21.5", 1920 * 1080, Core i5-8265U, Quad-core 1.6Ghz, Pcap. touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W3-CT	21.5", 1920 * 1080, Core i7-8565U, Quad-core 1.8Ghz, Pcap. touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W0-RT	21.5", 1920 * 1080, Celeron 4205U, Dual-core 1.8Ghz, Resistive touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W1-RT	21.5", 1920 * 1080, Core i3-8145U, Dual-core 2.1Ghz, Resistive touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W2-RT	21.5", 1920 * 1080, Core i5-8265U, Quad-core 1.6Ghz, Resistive touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
PPC-DS215-W3-RT	21.5", 1920 * 1080, Core i7-8565U, Quad-core 1.8Ghz, Resistive touch, 2*GLAN, 4*USB3.0, 3*COM, 2*HDMI, DC 12V, PSU
-4G / -8G / -16G	SO-DIMM, DDR4, 4GB/8GB/16GB Memory
-128GS / -256GS / -512GS	M.2 SSD: 128GB/256GB/512GB
	2.5" SATA SSD: 64GB/128GB/256GB/512GB/1TB
	2.5" HDD: 2TB/4TB
TBOX-AUDIO	Audio (Line out) connector on rear connector panel
TBOX-WiBlu	Wi-Fi with BT integrated module, with Antenna (M.2 interface)
EM06-E-PCKit	All network 4G/LTE module, With Antenna (M.2 interface)
	5G module, with Antenna (M.2 interface)
TBOX-9-36V	Optional 9-36V DC wide voltage input module with mains adaptor included
TBOX-SIMSLOT	Sim card slot for 3G/4G/5G wireless expansion, accepts full size (2FF) SIM cards

Packing List

■ 1x Standard Product
■ 1x 60W PSU (Power Supply)
■ 1x Power cable & Plug
■ 8x Panel mount metal clips

