

TMW110
Wall mount Temperature Transmitter

	1	2	3	4	5	6	7	8
	Wall mount Temperature Transmitter		TMW110			N	V	O
settings	1 Output Signals	4...20 mA 2-wire loop-powered		2				
	and display	• 4...20 mA 2-wire loop-powered, with display		4				
		Modbus RTU		M				
		• Modbus RTU, with display		N				
settings	2 Measured Parameter for Channel 1	T 0 ... +50°C (32 ... 122 °F)		1				
	and display ¹	T -5 ... +55°C (23 ... 131 °F)		2				
		T -40 ... +60°C (-40 ... 140 °F)		3				
		T special scale °C, please specify:		X				
		T special scale °F, please specify:		Y				
		No selection (Modbus model) ²		N	N	V	O	
acc.	6 User guide	No User's Guide						0
		• Multilingual Quick Guide for HMDW110 Series						I
hardware	7 Display options	Metric Units						1
		Non-Metric Units						2
		Metric units only (cannot be changed after delivery)						3
		No display						N
	8 Other options	No selection						N
		M12 connector instead of cable gland						B

1) Selects output parameter for analog output and the display (in devices with display)

2) Choose No selection (Modbus model) for Modbus devices without display

NOTE:	Selections in bold are included in the prices of the basic versions.
	• Selections in italic are available at an extra price.
	★ Suggested/default selection

LINKS:	User Guides
	Datasheet
	Vaisala.com product page

Example of order code with typical settings:

	1	2	3	4	5	6	7	8
Loop powered:	TMW110	2	3	N	V	O	O	N
Loop powered, display:	TMW110	4	3	N	V	O	O	1
Modbus, no display:	TMW110	M	N	N	V	O	O	N
Modbus, display:	TMW110	N	3	N	V	O	O	1

Accessories and spare parts

Conduit Fitting + O-Rin M16x1.5 / PG9, RE-MS
Conduit Fitting + O-Rin M16x1.5 / NPT1/2 Inch
USB Service Cable M8-4F, RS485
MI70 Connection Cable with M8-4F Connector
Terminal Block, Blue PK1304D 4P
Membrane Filter PC White UV stabilized
Porous PTFE Filter Ø12, L22mm

210674SP
210675SP
219690
219980SP
236620SP
ASM210856SP
DRW239993SP