

PTB110 Barometer

Selection	PTB110						PRICE
1 Pressure range	500–1100 hPa 600–1100 hPa 800–1100 hPa 600–1060 hPa 800–1060 hPa	1 2 3 4 5					
2 Output	0–5 V DC 0–2.5 V DC Frequency output		A B F				
3 Installation	Screw mount (standard installation) <i>DIN rail installation kit</i>			0 1			
4 Pressure fitting	Pressure connector barbed fitting for 1/8 inch hose (standard fitting) <i>Quick pressure connector with shutoff valve for 1/8 inch hose</i>				A B		
5 User guide	No user guide English user guide					A B	
TOTAL							
QTY							
TOTAL VALUE							

Accessories

Pressure connector barbed fitting for 1/8 inch hose
Quick pressure connector with shutoff valve for 1/8 inch hose
Dust filter, 3 pcs bag for barometer barbed fit
Static Pressure Head
Static Pressure Head Heated, 12 Volts
Static Pressure Head Heated, 24 Volts
[Link to online store](#)

Part number

19498SP
220186
237018SP
SPH10
SPH20
SPH20-24V

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

PTB110	1	A	0	A	B
--------	---	---	---	---	---

End customer: _____