www.esis.com.au
Ph 02 9481 7420
Fax 02 9481 7267
esis.enq@esis.com.au
ESIS Industrial Electronics

VAISALA

Order form G010062EN-B **Valid from 2026-03-23**
Purchaser Order no.

PTB330TS Barometric Pressure Transfer Standard

	Price
Vaisala BAROCAP® Barometric Pressure Transfer Standard **PTB330TS**	

Select below a configuration code for the PTB330 Barometer on the first row, for the MI70 Indicator on the second row and optionally for the HMP155 Probe on the third row.

PTB330 Digital Barometer for PTB330TS

				1	2	3	4	5	6	7	8	9	10	11	12	13	14	
	Vaisala BAROCAP® Digital Barometer		**PTB330**	**A**	**0**	**A**	**A**	**H**			**F**		**B**	**5**		**0**	**1**	Price
1	**Accuracy class**	**Class A**		**A**														
2	**Display**	**No display**			**0**													
3	**Power supply**	**10–35 V DC**				**A**												
4	**Signal output**	**RS-232 only, no analog output**					**A**											
5	**Pressure range**	**Barometer module** **500–1100 hPa**						**H**										
6	**2nd barometer module**	**No module**							**A**									
		Barometer module *500–1100 hPa*							*H*									
7	**3rd barometer module**	**No module**								**A**								
		Barometer module *500–1100 hPa*								*H*								
8	**Customer connection**	**8-pole M12 connector**									**F**							
9	**Pressure fitting**	**Barbed fitting 1/8", 1 barometer module**	Choose according									**E**						
		Barbed fitting 1/8", 2 barometer modules	to selection									**F**						
		Barbed fitting 1/8", 3 barometer modules	made above									**G**						
		Dust filter										**P**						
10	**Optional connection**	**Plugged**											**B**					
11	**Installation**	**PTB330TS in weatherproof hard case**												**5**				
12	**Calibration**	**ISO 9001 compliant factory calibration**													**A**			
		Accredited calibration for PTB330	(a separate service item PTB330NPC will be added)												*X*			
13	**Service contract**	**No service contract**														**0**		
14	**User Guide**	**No user guide**															**A**	
		PTB330TS User Guide in English															**1**	
		PTB330TS User Guide in German															**2**	
		PTB330TS User Guide in French															**3**	

Selections in bold are included in the price of the basic version.
Selections in italic are available at an extra cost.

Example of order code with typical settings:

PTB330	**A**	**0**	**A**	**A**	**H**	*H*	*H*	**F**	**G**	**B**	**5**	**A**	**0**	**1**

MI70 Handheld Indicator for PTB330TS

				1	2	3	
	Vaisala handheld indicator		**MI70**		**4**		Price
1	**Charger type**	**Euro AC adapter**		**B**			
		UK AC adapter		**C**			
		US AC adapter		**D**			
		AUS AC adapter		**E**			
		All AC adapters		**F**			
		JP AC adapter		**J**			
2	**Installation**	**PTB330TS**			**4**		
3	**Accessories**	**None**				**0**	
		MI70LINK software with RS-232 cable				*1*	
		MI70LINK software with USB cable				*4*	

Selections in bold are included in the price of the basic version.
Selections in italic are available at an extra cost.

Example of order code with typical settings:

MI70	**B**	**4**	*4*

Total value

Spare parts:
MI70 connection cable to HMT330, MMT330, DMT340, HMT100, PTB330 Item: 211339
MI70 battery Item: 26755

OPTIONAL (with additional price):

HMP155 Humidity and Temperature Probe for PTB330TS

				1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
	Vaisala HUMICAP® Humidity and Temperature Probe		**HMP155**	**E**	**1**	**A**	**A**			**A**			**0**			*C*	**4**	**A**	Price
1	**Probe type**	**RS-485 serial output**		**E**															
2	**Signal output selection**	**RS-485 serial output**			**1**														
3	**Analog output signal for CH1**	**None**				**A**													
4	**Analog output signal for CH2**	**None**					**A**												
5	**Units**	**Metric**						**1**											
		Non-metric						**2**											
6	**Humidity sensor type**	**General purpose**	**HUMICAP180R**						**1**										
		Composite sensor	*HUMICAP180RC*						*2*										
		General purpose	**HUMICAP R2**						**5**										
		Composite sensor	*HUMICAP R2C*						*6*										
7	**Heating options**	**None**								**A**									
8	**Chemical purge**	**None**									**0**								
		Manual purge with MI70 (only with composite sensor)									**4**								
9	**Sensor protection**	**Sintered Teflon filter**										**A**							
		Membrane filter										**B**							
10	**Probe cable length**	**No cable (no counter connector)**											**0**						
11	**Additional temperature probe**	**None**												**A**					
		Additional T-probe with 2 m cable												*B*					
12	**Calibration**	**At room temperature**													**1**				
		Accredited calibration for HMP155	*(a separate service item HMP155NPC will be added)*												**3**				
13	**PC accessories**	*MI70 connection cable*	*Item: 221801*													*C*			
14	**Installation**	**PTB330TS**															**4**		
15	**(For production use only)**																	**A**	
															Total value				

Selections in bold are included in the price of the basic version.
Selections in italic are available at an extra cost.

Example of order code with typical settings:

HMP155	**E**	**1**	**A**	**A**	**1**	**1**	**A**	**0**	**A**	**0**	**A**	**1**	*C*	**4**	**A**