

Document code:	G010057EN-B
Valid from:	December 2024

WXT530 - Vaisala Weather Transmitter WXT530 Series

	1	2	3	4	5	6	7	8	9	10	11	12	Price
Version / Model													
WXT536	Parameters: W, R, P, T, U	6											
WXT535	Parameters: R, P, T, U	5											
WXT534	Parameters: P, T, U	4											
WXT533	Parameters: W, R	3											
WXT532	Parameters: W	2											
WXT531	Parameters: R	1											
Communication Interface													
SDI-12 v 1.3, 1200 baud, 7, E, 1	A												
RS-232, Std. ASCII auto, 19200 baud, 8, N, 1	B												
RS-485, Std. ASCII polled, 19200 baud, 8, N, 1	C												
RS-485, Std. ASCII polled, 9600 baud, 8, N, 1	D												
RS-422, Std. ASCII auto, 19200 baud, 8, N, 1	E												
RS-422, NMEA 0183 v3.0, 4800 baud, 8, N, 1	G												
USB/RS-232, 1.4 m USB / M12 cable, ASCII auto, 19200, 8, N, 1	H												
USB/RS-485, 1.4 m USB / M12 cable, ASCII polled, 19200, 8, N, 1	J												
mA output 4-20 mA	K												
mA output 0-20 mA	L												
Reserved	M												
Reserved	N												
Reserved	P												
RS-485, NMEA 0183 v3.0, 4800 baud, 8, N, 1	R												
RS-485, ASCII auto with CRC, 4800 baud, 8, N, 1	T												
RS-485, Modbus RTU, server, 19200 baud, 8, E, 1	U												
Analog Interfaces													
None	1												
Analog outputs: 2 x 0-20mA for WS and WD	2												
Analog outputs: 2 x 4-20mA for WS and WD	3												
Analog inputs: Temp. SR. 10uV/W/m^2, Level (0-5 V), TB. (0.2 mm)	4												
Data Connector													
No connector (bushing and grounding accessories included)	A												
8-pin M12 male connector (bushing and grounding accessories included)	B												
No connector (no bushing and no grounding accessories)	C												
Heating													
None	1												
Heating	2												
User Profile													
Standard	A												
Cable													
No cable	1												
Shielded 2-meter long cable, 8-pin M12 connector in one end	2												
Shielded 10-meter long cable, 8-pin M12 connector in one end	3												
Shielded 10-meter long cable, 8-pin M12 connector in both ends	4												
Shielded 40-meter long cable, 12 wires, open ends on both cable ends (wiring using screw terminals)	5												
Shielded 50-meter long cable, 8-pin M12 connector in one end (24 V DC power supply must be used)	6												
Installation Accessories													
None	A												
Mounting Kit	B												
Bird Spike	C												
Mounting Kit and Bird Spike	D												
Supporting Software													
None	1												
Configuration tool for Windows + USB service cable	2												
Manual													
Online manual at docs.vaisala.com	A												
English Manual	B												
French Manual	C												
Japanese Manual	D												
Chinese Manual	E												
German Manual	F												
Russian Manual	G												
Packing													
Standard packing	1												
Reserved	2												
Packing including Russian language Formular (documentation for customs)	3												
Calibration Certificate													
None	A												
Factory Test Reports	B												
Accredited Wind Calibration (MEASNET)	C												
TOTAL													
QTY													
TOTAL VALUE													

Selections in bold are included in the prices of the basic versions.

Selections in italics are available at an extra price.

Example of order code with typical settings:

WXT530 6 A 1 A 1 A 1 A 1 A 1 A 1 A

End customer:

ACCESSORIES AND SPARE PARTS

220614	Vaisala Configuration Tool, USB Service cable SP
220782	Cable USB RS-232/485, 1.4 m USB / M12 SP
263193SP	Cable USB with power supply RS-232 / RS-485 USB/M12 SP / 100-240 V AC
222287	Cable 2 m Shielded 8-pin M12 SP
222288	Cable 10 m Shielded 8-pin M12 SP
CBL210679	Cable 10 m Shielded 8-pin M12, connectors on both ends SP
217020	Cable 40 m Shielded 12-pin, open end wires SP
245931	Cable 50 m Shielded 8-pin M12 SP (24 VDC power supply must be used)
CBL211021-10M	Cable 10 m M12/8(F) shielded, 36 mm open leads
CBL210021-2M	Cable 2 m M12/8(F) shielded, 36 mm open leads
222109	Bushing and Grounding Accessory Kit
212792	Mounting Kit
WMSFIX60	Mounting Accessory between Mounting kit and 60 mm tube
212793	Bird Kit
WSP150	Vaisala Surge Protector, no connectors
WSP152	Vaisala Surge Protector with connectors for 220782 and 215952
229104	Nokeval Converter
229110	Nokeval Programming Kit
218817SP	WXT Radiation Shield Set SP
WXTPTUSP	WXT PTU Module SP
224171	WXT Bottom Connector Kit SP
214273	Analog input connector SP, IP67, 8P, M12, Shielded
TM-PT1000	Temperature Sensor Tm-Pt1000 for WXT530 Series
WXT530BOTTOMDIGISP	WXT530 Bottom Assy with Digital Board SP
WXT530BOTTOMANAINSP	WXT530 Bottom Assy with Analog Input Board SP
WXT530BOTTOMMAOUTSP	WXT530 Bottom Assy with mA Output Board SP